# **Tyrone Camarero Specifications**



# Camerero DS2007H-28R

#### **Key features**

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Intel® C602 chipset
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM slots
- 2 PCI-E 3.0 x16, 3 PCI-E 3.0 x8,1 UIO PCI-E 3.0 x8 (for SMC UIO HBA) or 1 PCI-E 2.0 x4 (in x8)
- Intel® i350 Dual port GbE LAN
- 8x SATA2 and 2x SATA3 ports
- 8x SAS2 ports from LSI 2208
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- Dual port front and rear USB 3.0
- Performance boost with Hyper-Speed
- 8x 3.5" Hot-swap SAS / SATA Drive Bays
- 3x 80x38mm 4-pin PWM Fans
- 740W Redundant Power Supplies Platinum Level (94%)









## Processor/Cache

Processor Intel® Xeon® processor E5-2600 and

E5-2600 v2 family

## Chipset

Intel C602C chipset

#### **System Memory**

Memory Capacity 16x 240-pin DDR3 DIMM slots, Up to

1TB DDR3 ECC LRDIMM, Up to 512GB DDR3 ECC RDIMM,, Up to 128GB DDR3

ECC/non-ECC UDIMM

## **Expansion Slots**

PCI-Express 2 x PCI-E 3.0 x16, 3x PCI-E 3.0 x8,

1x PCI-E 2.0 x4 (in x8)

#### **Integrated On-Board**

SATA SATA 2.0 3Gb/s with RAID 0, 1, 5, 10,

SATA 3.0 6Gb/s with RAID 0, 1

SAS SAS2 from LSI 2208 (1GB cache), HW

RAID 0, 1, 5, 6, 10, 50, 60 support

LAN 2 RJ45 Gigabit Ethernet LAN ports,1

RJ45 Dedicated IPMI LAN port

## **Add-on Options**

Raid Card None
Optical Drive Optional

#### **Front Panel**

LED Indicators Power LED, Hard drive activity LED, 2x

Network activity LEDs, System Overheat

LED, Power fail LED

Buttons Power On/Off button, System Reset

button

## **Drive Bays**

HDD Bays 8x 3.5" HDD Bays SAS / SATA Drive Bays

Peripheral Drives Slim DVD-ROM drive (Optional)

## **Power Supply**

740W Redundant Power Supplies 80Plus Platinum Level (94%+)

## **Cooling System**

3x 80x38mm 4-pin PWM Fans

#### **Form Factor**

2U Rackmount

Width- 17.2" (437mm), Height- 3.5" (89mm), Depth – 25.5" (648mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com