Tyrone Camarero Specifications

Tyrone

Camerero DS200T36R-14RT

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family†
- Up to 1.5TB ECC DDR3, up to 1866MHz; 24x DIMM sockets
- 1 PCI-E 3.0 (x8) Low-profile, 1 PCI-E 3.0 (x16) & 1 PCI-E 3.0 (x8) Full-height slots
- Intel i350 Dual port GbE & Intel X540 Dual port 10GBase-T Controllers
- 4x Hot-swap 3.5" SAS/SATA HDD
- 750/700W Redundant Power Supplies 80 PLUS, Gold Level Certified







Processor/Cache

Processor Dual socket R (LGA 2011) supports

Intel® Xeon® processor E5-2600

and E5-2600 v2 family†

System Memory

Memory Capacity 24x 240-pin DDR3 DIMM sockets

> Up to 1.5TB DDR3 ECC LRDIMM Up to 768GB DDR3 ECC Registered

memory (RDIMM)

Expansion Slots

PCI-Express 1 PCI-E 3.0 (x8) Low-profile, 1 PCI-E

3.0 (x16) & 1 PCI-E 3.0 (x8) Full-height

slots

Integrated On-Board

SAS SAS from C606 RAID 0, 1, 10 support

SATA Via Cable for SATA controller SATA 2.0

3Gbps with RAID 0, 1, 5, 10 SATA 3.0

6Gbps with RAID 0, 1

LAN 2x RJ45 10GBase-T ports

> 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port

Add-on Options

RAID Card Optional

Optional **Optical Drive**

Front Panel:

LED Indicators Power LED, Hard drive activity LED, 2x

Network activity LEDs, System Overheat LED, Universal Information (UID) LED

Switches Power On/Off Button.System Reset

Button, UID Button

Drive bays

HDD bays 4x Hot-swap 3.5" SAS / SATA HDD trays

Slim DVD-ROM drive (optional) Peripheral Bays

Power Supply

750/700W Redundant Power Supplies 80 Plus, Gold Level

Certified

Cooling System

6x 4cm Counter-rotating PWM fans

Form Factor

1U Rackmount

Width 17.2" (437mm), Height 1.7" (43mm), Depth 27.75" (705mm)

> Email: info@tyronesystems.com For more/current product information, visit www.tyronesystems.com