Tyrone Camarero Specifications

Tyrone

Camarero DS200T3G1-210R

Key features

- Dual socket R (LGA 2011) supportsIntel® Xeon® processor E5-2600 and
- E5-2600 v2 family
- Up to 512GB ECĆ DDR3, up to1866MHz; 8x DIMM sockets
- 4x PCI-E 3.0 x16 slots (support GPU/Xeon Phi cards, opt.),1x PCI-E 3.0 x8 (in x16) slot, 1x PCI-E 2.0 x4 (in x16) slot
- · Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® i350 Dual-Port GbE Controller
- 10x Hot-swap 2.5" SATA Drive Bays
- 1800W Redundant Power Supplies 80Plus Platinum Level (94%+)
- 5x heavy duty cooling fans
- Smart server management tools
- Intel® Xeon Phi™ Support







Processor/Cache

Processor Dual socket R (LGA 2011) supports Intel®

Xeon® processor E5-2600 and E5-2600 v2

family

Chipset

Intel® C602 Chipset

System Memory

Memory Capacity 8x 240-pin DDR3 DIMM sockets

Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered

memory (RDIMM)

Expansion Slots

PCI-Express 4x PCI-E 3.0 x16 slots (support GPU/Xeon

Phi cards, opt.),1x PCI-E 3.0 x8 (in x16) slot,

1x PCI-E 2.0 x4 (in x16) slot

Integrated On-Board

SATA SATA 2.0 3Gbps with RAID 0, 1, 5, 10

SATA 3.0 6Gbps with RAID 0, 1, 5, 10

LAN 2 RJ45 Gigabit Ethernet LAN ports 1 RJ45

Dedicated IPMI LAN port

Add-on Options

RAID Card Optional

Optical Drive None

Front Panel:

LED Indicators

Power LED /Hard drive activity LED

/2x Network activity LEDs/

System Overheat LED
Power On/Off Button

Drive bays

Switches

HDD bays 10x 2.5" Hot-swap drive bays

Peripheral Bays None

Power Supply

1800W Redundant Power Supplies 80Plus Platinum Level (94%+)

Cooling System

5x 8cm heavy duty fans with optimal fan speed control

Form Factor

2U Rackmount, Height – 3.5" (89mm), Width - 17.2" (437mm),

Depth - 30.5" (775mm

Email: info@tyronesystems.com
For more/current product information, visit

www.tyronesystems.com