# **Tyrone Camarero Specifications**

## Camerero DS200T3W-14

# Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- Add on card support: 2x PCI-E 3.0 x16 full-height, Half-length slots
- Intel® i350 Dual port Gigabit Ethernet Controller; 2x LAN ports
- 4x Hot-swap 3.5" SAS/SATA2 HDD Bays Connected to on board storage controller
- 600W High-efficiency Power Supply Platinum Level (94%)









#### Processor/Cache

\_\_Dual\_socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family

### Chipset

Intel® C602 Chipset

### System Memory

16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM)

#### **Expansion Slots**

2x PCI-E 3.0 x16 full-height, Half-length slots

#### Integrated On-Board

SATA: Via Cable for SATA controller SATA 2.0 3Gbps with

RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1

LAN: 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45

Dedicated IPMI LAN port

#### Add-on Options

Raid card Optional

Optical Drive Optional

#### Front Panel:

LED Indicators: Power LED /Hard drive activity LED /2x Network activity LEDs / System Overheat LED

Switches:Power On/Off button System Reset button UID

button

## Drive bays

HDD bays 4x Hot-swap 3.5" SAS/SATA2 HDD Bays Peripheral Drive :Slim DVD-ROM drive (Optional)

# **Power Supply**

600W High-efficiency Power Supply Platinum Level (94%)

#### Cooling System

5x 4cm Counter-rotating PWM fans

#### Form Factor

1U Rackmount

Width 17.2" (437mm) Height 1.7" (43mm) Depth 25.6" (650mm)

Email: info@tyronesystems.com
For more/current product information, visit
www.tyronesystems.com