## **Tyrone Camarero Specifications**

# Tyrone

#### Camarero DS200T6T-212R

**Key Features:** 

Four hot-pluggable systems (nodes) in a 2U form factor. Each node supports the following:

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 1x PCI-E 3.0 (x16) low-profile slot
- Intel® i350 Dual port Gigabit Ethernet
- 3x 3.5" Hot-swap SATA3/SATA2 HDD Trays
- 1620W Redundant Power Supplies 80 PLUS, Platinum Level (94%)





#### Processor/Cache

Processor

Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2

family

#### Chipset

Intel® C602 Chipset

#### System Memory

Memory Capacity

8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered

memory (RDIMM)

#### **Expansion Slots**

PCI-Express

1x PCI-E 3.0 (x16) Low-profile slot

#### Integrated On-Board

SATA

SATA 2.0 & 3.0 with RAID 0, 1, 5, 10

LAN

2x RJ45 Gigabit Ethernet LAN ports 1x

RJ45 Dedicated IPMI LAN port

#### Add-on Options

RAID Card

Optional

Optical Drive

None

### Front Panel:

LED Indicators

2x Network activity LEDs Universal

Information (UID) LED

Buttons

Power On/Off button,System Reset button

UID button

#### Drive bays

HDD bays

3x 3.5" Hot-swap SATA3/SATA2 HDD Trays

Peripheral Bays

None

#### **Power Supply**

1620W Redundant Power Supplies 80 PLUS, Platinum Level (94%)

#### Cooling System

4x 8cm heavy duty PWM fans with optimal fan speed control

#### Form Factor

2U Rackmount, Width – 17.25" (438mm), Height - 3.47" (88mm), Depth - 26.75" (679mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com