Tyrone Camarero Specifications

Camarero DS200T6W-18R

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- Add on card support: 2x PCI-E 3.0 x16 Full-heigh, Half-length slots
- Intel® i350 Dual port Gigabit Ethernet Controller; 2x LAN ports
- 8x Hot-swap 2.5" SATA HDD bays for Customizable Storage
- 700W Redundant Power Supplies 80 PLUS, Gold Level Certified









Processor/Cache

Processor Dual socket R (LGA 2011) supports Intel®

Xeon® processor E5-2600 and E5-2600 v2

family

Chipset

Intel® C602 Chipset

System Memory

Memory Capacity 16x 240-pin DDR3 DIMM sockets

Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered

memory (RDIMM)

Expansion Slots

PCI-Express 2x PCI-E 3.0 x16 Full-heigh, Half-length slots

Integrated On-Board

SATA SATA 2.0 3Gbps with RAID 0, 1, 5, 10

SATA 3.0 6Gbps with RAID 0, 1, 5, 10"

2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port

Add-on Options

RAID Optional Optical Drive None

Front Panel:

LED Indicators Power LED, Hard drive activity LED,

2x Network activity LEDsm,

Universal Information (UID) LED

Switches Power On/Off Button

Drive bays

HDD bays 8x Hot-swap 3.5" SAS / SATA HDD

trays (ready for PCI-E SAS controller card)

Peripheral Bays Slim DVD-ROM drive (optional)

Power Supply

700W Redundant Power Supplies80 PLUS, Gold Level Certified

Cooling System

5x 4cm Counter-rotating PWM Fans

Form Factor

1U Ractmount Width 17.2" (437mm), Height 1.7" (43mm),

Depth 23.5" (597mm)

Email: info@tyronesystems.com

For more/current product information, visit www.tyronesystems.com