

Tyrone Camarero Specifications

Tyrone[®]

JBOD JS12RE1-212R

Key features

- 2U Storage JBOD Chassis with capacity 12 x 3.5" hot-swappable HDDs bays
- Single Expander Backplane Boards support SAS3/2 or SATA3 HDDs with 12Gb/s throughput
- 4 x Mini-SAS HD ports for Internal /External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 740W (1+1) 95% efficient Platinum level power supplies
- 3 x 80mm high efficient hot-swappable fans for best system cooling
- Ideal for Cloud backup, data Replication or High density Archive Storage Applications



Backplane

Backplane BPN-SAS3-826EL1 (SAS3 12Gb/s single expander backplane, with LSI SAS3 expander, support 12x 3.5" SATA3/SAS2/SAS3 drives, with 4x mini-SAS3 HD connectors)

Drive Bays Supported

Up to 12 x 3.5" hot-swap HDD bays for JBOD solution

Front Panel

LED 1 Network Activity LEDs

Buttons Power On/Off button, System Reset button, Unit Identification (UID) button

Power Supply

740W (1+1) 95% efficient Platinum level power supplies

Cooling System

3 x 80x38mm hot-swap cooling fan

Form Factor

2U Rackmount
Width:17.2" (437mm),
Height:3.5" (89mm),
Depth :25.5" (647mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com