

Tyrone Camarero Specifications

Camarero SS200T3R-12

Tyrone[®]

Key features

- Single socket H2 (LGA 1155) supports Intel® Xeon® E3-1200 & E3-1200 v2 series, 2nd and 3rd Gen Core i3 processors***, Pentium, Celeron
- Intel® C202 PCH chipset
- Up to 32GB DDR3 ECC 1333MHz /1600MHz*** UDIMMs in 4 sockets
- Intel® 82579LM and 82574L, 2x Gigabit Ethernet LAN ports
- 6x SATA 2.0 with RAID 0, 1, 5, 10
- 2x (x8) PCI-E 3.0*** in x8 slots and 1x (x4) PCI-E 2.0 in x8 slot
- 9x USB 2.0 ports ((2 rear + 6 via header + 1 Type-A)
- 2 x 3.5" Internal Drive Bay
- 2x 10cm 4200 RPM Fan
- 260W Power Supply



Processor/Cache

Processor	Intel® Xeon® E3-1200 & E3-1200 v2 series, 2nd and 3rd Gen Core i3 processors***, Pentium, Celeron
-----------	---

Chipset

Intel® C202 PCH chipset

System Memory

Memory Capacity	4x 240-pin DDR3 DIMM sockets, Supports up to 32 GB DDR3 ECC Un-Buffered memory (UDIMM)
-----------------	--

Expansion Slots

PCI-Express	1x (x8) PCI-E 3.0
-------------	-------------------

Integrated On-Board

SATA	6x SATA2 (3Gb/s) w/ RAID 0, 1, 5, 10
LAN	LAN: 2x Gigabit Ethernet LAN ports: Intel® 82579LM and Intel® 82574L

Add-on Options

RAID Card	Optional
Optical Drive	Optional

Front Panel :

Buttons	Power On/Off button, System Reset button
LEDs	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED

Drive bays

HDD bays	2 x 3.5" Internal Drive Bay
----------	-----------------------------

Power Supply

260W Power Supply

Cooling System

2x 10cm 4200 RPM blower fans

Form Factor

1U Rackmount Formfactor
Width- 16.8" (426mm) ,
Height- 1.7" (43mm) ,
Depth – 22.6" (574mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com