Tyrone Camarero Specifications

Tyrone

Camarero SS2C0T3R-14R

Key features

- Single socket H2 (LGA 1155) supports Intel® Xeon® E3-1200 & v2 series 2nd Gen Core i3 processors®
- Intel® C202 PCH Chipset
- 4x 3.5" Hot-swap SATA2 HDDs
- 1x PCI-E 3.0* x8 Full-height slot
- Up to 32GB DDR3 ECC 1333MHz / 1600MHz* UDIMMs in 4 sockets
- Intel® 82579LM and 82574L, 2x Gigabit Ethernet LAN ports
- IPMI 2.0 on Dedicated LAN port
- 6x SATA 2.0 with RAID 0, 1, 5, 10
- · 400W Redundant Power Supplies
- Disk-on-module (DOM) power connector







Processor/Cache

Processor Intel® Xeon® processor E3-1200 & v2 series,

Intel® 2nd Gen Core i3 processors

Chipset

Intel® C202 PCH chipset

System Memory

Memory Capacity 4x 240-pin DDR3 DIMM sockets
Supports up to 32 GB DDR3 ECC Un-Buffered memory
(UDIMM)

Expansion Slots

PCI-Express 1x PCI-E 3.0* x8 Full-height slot

Integrated On-Board

SATA 6x SATA2 (3Gbps) w/ RAID 0, 1, 5, 10

LAN 2x RJ45 LAN ports 1x RJ45 Dedicated

IPMI LAN port

Add-on Options

RAID Optional optical drive Optional

Front Panel:

LED Indicators Power LED/Hard drive activity LED

/2x Network activity LEDs
/ System Overheat LED

Buttons Power On/Off button, System Reset button

Drive bays

HDD bays 4x 3.5" Hot-swap SATA2 HDDs w/ RAID

Peripheral Bays Optional

Power Supply

400W Redundant Power Supplies

Cooling System

4x 4cm 12,500 RPM PWM fans

Form Factor

1U Rackmount, Height – 1.7" (43mm). Width - 17.2" (437mm), Depth - 19.8" (503mm)

Email: info@tyronesystems.com
For more/current product information, visit
www.tyronesystems.com