Tyrone Camarero Specifications

Tyrone®

Camarero SS2iOTR-310

Key features

- Gaming, Digital Imaging, Entry-Level Worksation, Simulation and Creation Design
- Single socket R3 (LGA 2011) supportsIntel® Core™ i7 Processor Extreme Edition and X-Series, Intel® Xeon® processor E5-2600 v4/ v3, E5-1600 v3
- Intel® X99 Chipset
- Up to 128GB non-ECC UDIMM DDR4, frequency up to 3300MHz (OC);8x DIMM slots
- 4 PCI-E 3.0 x16, 2 PCI-E 2.0 x1 (in x4)
- ALC 1150 HD Audio
- Removable 3.5" and 2.5" HDD/SSD cages with tool-less trays for up to 10 drives; 2x 5.25"Peripheral Drive Bays
- Dual GbE LAN with Intel® I210-AT
- 2x 12cm front cooling fans, 1x 12cm rear exhaust fan
- 750W Multi-output Power Supply





Processor/Cache

Processor Single socket R3 (LGA 2011) supports Intel® Core™ i7 Processor Extreme

Edition and X-Series,

Intel® Xeon® processor E5-2600 v4/ v3,

E5-1600 v3

Chipset

Chipset Intel® X99 Chipset

System Memory

Memory Capacity 8x 288-pin DDR4 DIMM slots,

Supports up to 128GB DDR4 Non-ECC Un-Buffered memory (UDIMM)

in 8 DIMM slots

Expansion Slots

PCI-Express 4 PCI-E 3.0 x16, 2 PCI-E 2.0 x1 (in x4)

Integrated On-Board

SATA SATA3 (6Gbps) via Intel X99 controller,

10x SATA3 ports: 6x iSATA (RAID 0, 1, 5, 10) and 4x sSATA

LAN 2x RJ45 Gigabit Ethernet LAN ports

Add-on Options

Raid Optional Optical Drive Optional

Front Panel

LED Indicators Power LED, Hard drive activity LED

Buttons Power On/Off button, Reset button

Drive Bays

HDD bays 3.5" and 2.5" HDD/SSD cages with

tool-less trays for up to 10 drives

Peripheral Bays 2x 5.25" Peripheral Drive Bays

Power Supply

750W Multi-output Power Supply

Cooling System

2x 12cm front cooling fans, 1x 12cm rear exhaust fan

Form Factor

Form Factor Mid-Tower

Height : 18.1" (460mm),

Width : 7.9" (201mm),

Depth : 19.4" (493mm)

Email: info@tyronesystems.com
For more/current product information, visit
www.tyronesystems.com