Tyrone Camarero Specifications

Camarero SS300TR-14LT

Key features

- 0°~60°C (board level) Operation Temperature, 7-year lifespan, Support 12V only power supply, Two 4-pin internal power (output) connectors, One M.2 connector to support 22110, 2280 and 2242 modules
- Single socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/v3 and E5-1600 v4/v3 family
- Intel® C612 chipset
- Up to 512GB ECC 3DS LRDIMM, up to DDR4-2400 MHz; 4xDIMM slots
- 1 PCI-E 3.0 x16, 2 PCI-E 3.0 x8
- Intel® X550 Dual 10GBase-T LAN ports
- 10x SATA3 (6Gbps) via C612
- 1x VGA, 2x COM, 1x TPM
- 5x USB 3.0 ports, 6x USB 2.0 ports
- 2x SuperDOM with built-in power
- 4 x 3.5" hot-swap SAS/SATA
- 4 x 40x28mm PWM fan(s)
- 400W Redundant Power Supply Platinum with PMBUS, W54.5xL220xH40mm









Processor/Cache

Single socket R3 (LGA 2011) supports Processor

Intel® Xeon® processor E5-2600v4/v3

and E5-1600 v4/v3 family

Chipset

Chipset Intel® C612 chipset

System Memory

Memory Capacity 4x 288-pin DDR4 DIMM slots, Up to

512GB ECC 3DS LRDIMM, Up to 256GB ECC LRDIMM, Up to 128GB ECC RDIMM

Expansion Slots

PCI-Express 1 PCI-E 3.0 x16, 2 PCI-E 3.0 x8

Integrated On-Board

SATA SATA3 (6Gbps) via C612 controller RAID

0, 1, 10 support

IAN 2x RJ45 10GBase-T Ethernet LAN ports,

1x RJ45 Dedicated IPMI LAN port

Add-on Options

Raid Optional **Optical Drive** Optional

Front Panel

LED Indicators 2 Network Activity LEDs, HDD activity LED,

Power Status LED, System Information LED

Buttons Power On/Off button, System Reset button

Drive Bays

HDD bays 4 x 3.5" hot-swap SAS/SATA

Peripheral Drives Optional 1 x Slim DVD-ROM Drive,

Optional 1 x USB + COM port tray

Power Supply

400W Redundant Power Supply Platinum with PMBUS, W54.5xL220xH40mm

Cooling System

4 x 40x28mm PWM fan(s)

Form Factor

1U Rackmount Form Factor

Width: 17.2" (437 mm), Height: 1.7" (43 mm), 19.85" (503 mm) Depth:

Email: info@tyronesystems.com For more/current product information, visit www.tyronesystems.com

O Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries

O Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks .All other brands and names are the property of their respective owners