

Tyrone Camarero Specifications

Camarero SS30iTZ-34

Key features

- Intel® 6th Generation Core™ i3 series, Intel® 6th Generation Core™ i5 series, Intel® 6th Generation Core™ i7 series, Intel® 7th Generation Core™ i3 series, Intel® 7th Generation Core™ i5 series, Intel® 7th Generation Core™ i7 series. , Socket H4 (LGA 1151) supported, CPU TDP support Up to 115W TDP
- Intel® Z170 Express
- 64GB Unbuffered non-ECC UDIMM, DDR4-3200MHz (OC), in 4 DIMM slots
- 1 PCI-E 3.0 x16, 1 PCI-E 3.0 x4, 1 PCI-E 3.0 x1
- 1 DVI - D port, 1 DP (DisplayPort) port, 1 HDMI port, ***Display Port support up to DP1.2, HDMI support up to HDMI1.4***
- Intel ® Z170 Express controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10 + 1 PCI-E M.2(PCI-E x4, 2260/2280 /22110)(No Raid Support)
- Single LAN with Intel® single Ethernet PHY i219V
- 4 x 3.5" Internal Drive Bay, Optional 4 x 2.5" fixed drive bay
- 1 x 12cm rear exhaust fan(s), Optional 1 x 12cm (front) cooling fan
- 900W Gold Level Certified High-Efficiency Power Supply

Tyrone®



Processor/Cache

Processor	Intel® 6th Generation Core™ i3 series, Intel® 6th Generation Core™ i5 series, Intel® 6th Generation Core™ i7 series, Intel® 7th Generation Core™ i3 series, Intel® 7th Generation Core™ i5 series, Intel® 7th Generation Core™ i7 series. , Socket H4 (LGA 1151) supported, CPU TDP support Up to 115W TDP
-----------	--

Chipset

Chipset	Intel® Z170 Express
---------	---------------------

System Memory

Memory Capacity	64GB Unbuffered non-ECC UDIMM, DDR4-3200MHz (OC), in 4 DIMM slots
-----------------	---

Expansion Slots

PCI-Express	1 PCI-E 3.0 x16, 1 PCI-E 3.0 x4, 1 PCI-E 3.0 x1
-------------	---

Integrated On-Board

SATA	Intel® Z170 Express controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10 + 1 PCI-E M.2(PCI-E x4, 2260/2280 /22110) (No Raid Support)
LAN	1 RJ45 Gigabit Ethernet LAN ports

Add-on Options

Raid Card	Optional
Optical Drive	Optional

Front Panel

LED Indicators	1 Network Activity LEDs, HDD activity LED, Power LED, System Information LED
Buttons	Power On/Off button

Drive Bays

HDD bays	4 x 3.5" Internal Drive Bay, Optional 4 x 2.5" fixed drive bay
Peripheral Bays	2 x standard 5.25" drive bay, 1 x 3.5" internal fixed drive bay

Power Supply

900W Gold Level Certified High-Efficiency Power Supply
--

Cooling System

1 x 12cm rear exhaust fan(s), Optional 1 x 12cm (front) cooling fan
--

Form Factor

Form Factor	Mid-tower
Width:	7.6" (193 mm),
Height:	16.7" (424 mm),
Depth:	20.68" (525 mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com