

# Tyrone Camarero Specifications

Camarero SS4007E1-445R

## Key features

- **Backup Storage, Cold Storage, Database Applications, Data Warehousing, Archiving**
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 165W
- Intel® C621 chipset
- Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots;  
Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)
- 2 PCI-E 3.0 x8 (in x16), 3 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8), 1 PCI-E 3.0 x8 (occupied by HBA)
- 2 GbE LAN ports via Intel i210
- 45 Hot-swap 3.5" SAS3/SATA3 drive bays, 2 rear Hot-swap 2.5" SATA drive bays; optional 2 SATA or NVMe
- Broadcom 3108 SAS3, HW RAID, (AOC-S3108L-H8IR-P)
- Server remote management: IPMI 2.0/ KVM over LAN / Media over LAN
- 5 Hot-swap 8cm redundant PWM fans
- 1600W Redundant Power Supplies Platinum Level



### Processor/Cache

Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Single Socket P (LGA 3647) supported, CPU TDP support 165W
-----------	--

### Chipset

Chipset	Intel® C621 chipset
---------	---------------------

### System Memory

Memory Capacity	Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots; Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)
-----------------	--

### Expansion Slots

PCI Express	2 PCI-E 3.0 x8 (in x16), 3 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8), 1 PCI-E 3.0 x4 (occupied by HBA card)
-------------	--

### Integrated On-Board

SAS	Broadcom 3108 SAS3, HW RAID, (AOC-S3108L-H8IR-P)
SATA	SATA3 (6Gbps) via Intel® C621 controller RAID 0, 1, 5, 10 support
LAN	2 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 Dedicated IPMI LAN port

### Add-on Options

Optical Drive	None
---------------	------

### Front Panel

LED	Power LED, Hard drive activity LED, Network activity LEDs, System Overheat LED, Power fail LED
Buttons	Power On/Off button, System Reset button

### Drive Bays

HDD Bays	45 Hot-swap 3.5" SAS3/SATA3 drive bays, 2 Rear Hot-swap 2.5" SATA3 drive bays
Optional	2 Hot-swap 2.5" NVMe/SATA drive bays (rear)

### Power Supply

1600W Redundant Power Supplies Platinum Level
---

### Cooling System

5 High-performance 80mm cooling fans
--------------------------------------

### Form Factor

Form Factor	4U Rackmount
Width	17.2" (437mm),
Height	7" (178mm),
Depth	26" (660mm)

Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)

For more/current product information, visit

[www.tyronesystems.com](http://www.tyronesystems.com)