

Tyrone Camarero Specifications

Tyrone[®]

Camarero SSi00TO-34

Key features

- Single socket H4 (LGA 1151) supports Intel® 7th/6th Gen. Core™ i7/i5/i3 series, Intel® Celeron® and Intel® Pentium®
- Intel® Z170 Express Chipset
- Up to 64GB Non-ECC UDIMM, DDR4-3300MHz (OC), in 4 DIMM slots
- Single GbE LAN port (Intel® i219V), Single GbE LAN port (Intel® I210-AT)
- 6 SATA3 (6Gbps); RAID 0, 1, 5, 10
- 3 PCI-E 3.0 x16 (run at 16/NA/16 or 16/8/8), 2 PCI-E 3.0 x1 (in x4) slots
- 1 PCIe M.2 (PCIe x4, support 2260/2280/22110)
- 4 USB 3.0 (2 rear + 2 via header), 6 USB 2.0 (2 rear + 4 via headers), 1 USB 3.1 (10Gbps) Type C (rear), 2 USB 3.1 (10Gbps) ports (headers)
- 1 DVI-D, 1 DP (Display Port), 1 HDMI 1.4
- HD Audio 7.1 channel connector by Realtek ALC1150
- UEFI BIOS support
- 4 x 3.5" fixed drive bay, Optional 4 x 2.5" fixed drive bay
- PS2/ATX 500W Multi-output power supply with 12CM fan, Bronze level



Processor/Cache		Front Panel	
Processor	Single socket H4 (LGA 1151) supports Intel® 7th/6th Gen. Core™ i7/i5/i3 series, Intel® Celeron® and Intel® Pentium®	LED Indicators	1 Network Activity LEDs, HDD activity LED, Power Status LED, System Overheat LED
Chipset	Intel® Z170 Express Chipset	Buttons	Power On/Off button
System Memory		Drive Bays	
Memory Capacity	4x 288-pin DDR4 DIMM slots, Supports up to 64GB DDR4 Non-ECC Un-Buffered memory (UDIMM) in 4 DIMM slots	HDD Bays	4 x 3.5" fixed drive bay, Optional 4 x 2.5" fixed drive bay
Expansion Slots		Peripheral Bays	2 x standard 5.25" drive bay, 1 x 3.5" internal fixed drive bay
PCI-Express	3 PCI-E 3.0 x16 (run at 16/NA/16 or 16/8/8), 2 PCI-E 3.0 x1 (in x4) slots	Power Supply	
Integrated On-Board		PS2/ATX 500W Multi-output power supply with 12CM fan, Bronze level	
SATA	SATA3 via PCH w/ RAID 0, 1, 5, 10	Cooling System	
LAN	2x RJ45 Gigabit Ethernet LAN ports	1 x 12cm rear exhaust fan(s), Optional 1 x 12cm (front) cooling fan	
Add-on Options		Form Factor	
Raid Card	Optional	Form Factor	Mid-tower
Optical Drive	Optional	Height	: 16.7"(424 mm),
		Width	: 7.6" (193 mm),
		Depth	: 20.68"(525 mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	