

Tyrone Camarero Specifications

Tyrone®

Camarero SSi00TO-34L

Key features

- Intel® 6th Generation Core™ i3 series, Intel® 6th Generation Core™ i5 series, Intel® 6th Generation Core™ i7 series, Intel® 7th Generation Core™ i3 series, Intel® 7th Generation Core™ i5 series, Intel® 7th Generation Core™ i7 series. , Socket H4 (LGA 1151) supported, CPU TDP support Up to 160W
- Intel® Z170 Express
- 64GB Unbuffered non-ECC UDIMM, DDR4-3300MHz (OC), in 4 DIMM slots
- 3 PCI-E 3.0 x16, 2 PCI-E 3.0 x1, 3 PCI-Ex16 slots are running at 16/NA/16 or 16/8/8, 2 PCI-E x1 are in x4 slots
- 1 DVI - D port, 1 DP (DisplayPort) port, 1 HDMI port, Display Port support up to DP1.2, HDMI support up to HDMI1.4b(will free upgrade to HDMI2.0 in 2016)
- Intel® Z170 Express controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10+ 1 PCI-E M.2 (PCI-E x4, 2260/2280/22110)(No Raid Support)
- Single LAN with Intel® Ethernet Controller I210-AT, Single LAN with Intel® single Ethernet PHY i219V
- 6 x 3.5" fixed drive bay, 4 x 2.5" fixed drive bay
- 3x 120mm PWM fans included
- PS2 750W Multi-output Power Supply for Desktop, semi-modular cable output



Processor/Cache

Processor	Intel® 6th Generation Core™ i3 series, Intel® 6th Generation Core™ i5 series, Intel® 6th Generation Core™ i7 series, Intel® 7th Generation Core™ i3 series, Intel® 7th Generation Core™ i5 series, Intel® 7th Generation Core™ i7 series. , Socket H4 (LGA 1151) supported, CPU TDP support Up to 160W
-----------	--

Chipset

Chipset	Intel® Z170 Express
---------	---------------------

System Memory

Memory Capacity	64GB Unbuffered non-ECC UDIMM, DDR4-3300MHz (OC), in 4 DIMM slots
-----------------	---

Expansion Slots

PCI-Express	3 PCI-E 3.0 x16, 2 PCI-E 3.0 x1, 3 PCI-Ex16 slots are running at 16/NA/16 or 16/8/8, 2 PCI-E x1 are in x4 slots
-------------	---

Integrated On-Board

SATA	Intel® Z170 Express controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10, +1 PCI-E M.2 (PCI-E x4, 2260/2280/22110) (No Raid Support)
LAN	2 10G SFP+ ports, 1 RJ45 Dedicated IPMI LAN port

Add-on Options

Raid Card	Optional
Optical Drive	Optional

Front Panel

LED Indicators	HDD activity LED, Power Status LED
Buttons	Power On/Off button, System Reset button

Drive Bays

HDD bays	6 x 3.5" fixed drive bay, 4 x 2.5" fixed drive bay
Peripheral Bays	2 x standard 5.25" drive bay

Power Supply

PS2 750W Multi-output Power Supply for Desktop, semi-modular cable output

Cooling System

2 x 12cm front cooling fan(s), 1 x 12cm rear exhaust fan(s)

Form Factor

Form Factor	Mid-Tower
Height	: 18.1" (460 mm),
Width	: 7.9" (200 mm),
Depth	: 19.4" (493 mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com