# **Tyrone Camarero Specifications**

Camarero AD00TR-54i

# Key features

- EATX Server Board with dual Xeon Scalable processors
- Intel C621
- DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)
- . 5 PCle x16 (Gen3) and one PCle x8 (Gen3) for three double-deck cards
- LAN1: Intel I210AT , LAN2: Intel I210AT, 10/100/1000 Mbps, 2 x RJ-45
- 10 SATA3 and six USB3.0 ports
- One M.2 2280 (SATA / PCle compatible)
- 0 ~ 40 °C ambient operation temperature range
- 3 x 5.25" bays to 4 x hot-plug SAS/SATA 12G LFF bays/Hot swap bays
- Front:120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
- 1200W Single PS, 80Plus Platinum







Đ٢	00	es	20	F/I	. 2	~	10
ш	UL	63	30	LA	Ja	9	ш

Processor EATX Server Board with

dual Xeon Scalable processors

#### Chipset

Chipset Intel C621

#### System Memory

Memory Capacity

DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)

# **Expansion Slots**

PCI-Express

5 PCle x16 (Gen3) and one PCle x8 (Gen3) for three

double-deck cards

# **Integrated On-Board**

SATA 10 x SATAIII (RAID 0,1,5,10)

LAN Intel I210AT; LAN2: Intel I210AT

#### **Add-on Options**

Raid Card Support RAID 0,1,5,6,10,50&60

Via optional AOC

Optical Drive Optional

Front Panel

Front Panel Front Control Panel Power Switch,

System Reset

Buttons Power On/Off button

**Drive Bays** 

Drive Bays 3 x 5.25" bays to 4 x hot-plug

SAS/SATA 12G LFF bays/Hot swap bays

Peripheral Drives Optional

### **Power Supply**

1200W Single PS, 80Plus Platinum

# **Cooling System**

Front 120 x 25 mm x1 PWM Fan
Rear 120 x 25 mm x1 PWM Fan

#### **Form Factor**

Form Factor 5U Rackmount/tower/Convertable

Dimensions 560 x 200 x 430 mm (22" x 7.9" x 16.9")

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com