

Tyrone Camarero Specifications

Tyrone

Camerero: ADI10A3N-14

Key Feature

- Intel® Ice Lake-SP Processors, Supports CPU TDP up to 270W
- Intel® C621A
- DDR4 3200/2933/2666/2400 (1DPC/2DPC) MHz, Total 16+16 DIMM slots (2DPC)), Up to 12TB 3DS ECC RDIMM/LRDIMM
- 2 PCIe4.0 x16
- 1 x 4-port SATA/SAS/NVMe backplane with 1 x SFF-8643 + 2x SFF-8654(Slimline 8i) connectors
- RC-PE1U02-Z2 : 1 x16 PCIe slot
- 14 x SATA 6.0 Gb/s
- 1 x GbE RJ45
- 4 x 3.5"/2.5" hot swap (SAS/SATA/NVMe), 1 x M.2
- 8 x 40x56mm easy swap fans
- 800W/1200W 1+1 redundant power supply 80+ Platinum



| Processor/Cache | | Front Panel | |
|---------------------|---|--|---|
| Processor | Intel® Ice Lake-SP Processors, Supports CPU TDP up to 270W | Front Panel | System power on/off, System ID, System reset, 2 x USB 3.2 Gen1 Type A |
| Chipset | | Ports | 1xGbE RJ45, 2x USB 3.0 typA, 1 x VGA, 1 x Serial port |
| Chipset | Intel C621A chipset | LEDs | Power status, System alert, System ID |
| System Memory | | Drive bays | |
| Memory Capacity | DDR4 3200/2933/2666/2400 (1DPC/2DPC) MHz, Total 16+16 DIMM slots (2DPC)), Up to 12TB 3DS ECC RDIMM/LRDIMM | HDD Bays | 4 x 3.5"/2.5" hot swap (SAS/SATA/NVMe), 1 x M.2 |
| Expansion Slot | | Power Supply | |
| PCI-Express | 2 PCIe4.0 x16 | Power Supply | 800W/1200W 1+1 redundant power supply 80+ Platinum |
| Integrated Onboard: | | Cooling System | |
| SATA | 14 x SATA 6.0 Gb/s | | 8 x 40x56mm easy swap fans |
| LAN | 1 x GbE RJ45 | Form Factor | |
| Add-on Options | | Form Factor | 1U Rackmount |
| Raid Card | Optional | Dimensions | |
| Optical Drive | None | Dimensions | (W x D x H) : 615 x 1135 x 273 |
| | | Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com | |