

Tyrone Camarero Specifications



Camerero: ADI200A3R-212

Key Feature

- 4th/5th Gen Intel® Xeon Dual Processor
- 16 x DDR5 5600/4800MHz RDIMM(1 DPC) , Support up to 4TB(3DS RDIMM)
- 5 x16 PCIe5.0 , 1 x8 PCIe5.0 , 3 x8 MCIO PCIe5.0
- 2 x SATA3.0 (6 Gb/s) 7pin connectors, 1 x Slimline connector (up to 8 SATA ports)
- 1 x RJ45 GbE connector for BMC dedicate management port
- 2 x Broadcom BCM5720 based 1GbE
- 2 x USB3.1 Gen1 double stack type-A connector at rear I/O, USB 3.0 Gen1 on Front side
- 12 x front loaded 2.5"/3.5" bays(SAS/SATA)
- Support CRPS PSU(FSP) 800W/1200W/1600W



Processor/Cache		Front Panel	
Processor	4th/5th Gen Intel® Xeon Dual Processor	Front LEDs	1 x Power Status,1 x HDD Activity, 2 x LAN Activity,1x UID
System Memory		Power Buttons	Power Button, Reset Button, UID Button, USB 3.0 x 2
Memory Capacity	16 x DDR5 5600/4800MHz RDIMM(1 DPC) , Support up to 4TB(3DS RDIMM)	Drive bays	
Expansion Slot		HDD Bays	12 x 3.5 /2.5(SAS/SATA) Hot Swappable Bays
PCI-Express	5 x16 PCIe5.0 , 1 x8 PCIe5.0 , 3 x8 MCIO PCIe5.0, 2 x M.2 2280 PCIe Gen4.0 x4 (Onboard)	Power Supply	
Integrated Onboard		Power Supply	Support CRPS PSU(FSP) 800W/1200W/1600W
SATA	2 x SATA3.0 (6 Gb/s) 7pin connectors, 1 x Slimline connector (up to 8 SATA ports)	Form Factor	
		Form Factor	2U Rackmount
		Dimensions	
		Dimensions	660 x 436 x 87 mm
Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com			

◦ Intel, the Intel logo,the Intel Inside logo,Xeon,and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and /Or other Countries
◦ Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the properties of their respective owners