

# Tyrone Camarero Specifications

# Tyrone

## Camerero: ADI200C3A-54

### Key Feature

- 4th/5th Gen Intel® Xeon Dual Processor
- 16 x DDR5 5600/4800MHz RDIMM(1 DPC) , Support up to 4TB(3DS RDIMM)
- 5 x16 PCIe5.0 , 1 x8 PCIe5.0 , 3 x8 MCIO PCIe5.0
- 2 x SATA3.0 (6 Gb/s) 7pin connectors, 1 x Slimline connector (up to 8 SATA ports)
- 1 x RJ45 GbE connector for BMC dedicate management port
- 2 x Broadcom BCM5720 based 1GbE
- 2 x USB3.1 Gen1 double stack type-A connector at rear I/O, USB3.0 Gen1 on Front Side
- 8 x Hot-swap 3.5"/2.5" drive bays SAS/SATA, 2 x M.2 SSD 2280 PCIe4.0 x4
- (1+1) 1300/1600 80+ Redundant Power Supplies



Processor/Cache		Front Panel	
Processor	4th/5th Gen Intel® Xeon Dual Processor	Front I/O Ports	1 x Power Button, 1 x Reset Button, 2 x USB 3.0, 1 x System Power LED Button
GPU		Rear I/O Ports	2 x 1000Base-T Ethernet Ports, 1 x 1000Base-T Dedicated Server Management Port, 2 x USB 3.1 Gen1 Type-A Port, 1 x DB-15 VGA connector, 1 x UID LED Button, 1 x External UID/switch button
GPU	RTX 4000/5000/6000 Ada	Power Supply	
System Memory		Power Supply	(1+1) 1300/1600 80+ Redundant Power Supplies
Memory Capacity	16 x DDR5 5600/4800MHz RDIMM(1 DPC) , Support up to 4TB(3DS RDIMM)	Form Factor	
Expansion Slot		Form Factor	4U Rackmount/Tower
PCI-Express	5 x16 PCIe5.0 , 1 x8 PCIe5.0 , 3 x8 MCIO PCIe5.0, 2 x M.2 2280 PCIe Gen4.0 x4 (Onboard)	Dimensions	
Integrated Onboard:		Dimensions	680 x 438 x 175 mm
SATA/SAS	2 x SATA3.0 (6 Gb/s) 7pin connectors, 1 x Slimline connector (up to 8 SATA ports)	Email : <a href="mailto:Info@tyronesystems.com">Info@tyronesystems.com</a> For more/current product information, Visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a>	