

Tyrone Camarero Specifications

Tyrone

Camerero: ADI200F0A-55

Key Feature

- 4th/5th Gen Intel® Xeon Dual Processor
- 16 x DDR5 5600/4800MHz RDIMM(1 DPC) , Support up to 4TB(3DS RDIMM)
- 5 x16 PCIe5.0 , 1 x8 PCIe5.0 , 3 x8 MCIO PCIe5.0
- 2 x SATA3.0 (6 Gb/s) 7pin connectors, 1 x Slimline connector (up to 8 SATA ports)
- 1 x RJ45 GbE connector for BMC dedicate management port
- 2 x Broadcom BCM5720 based 1GbE
- 2 x USB3.1 Gen1 double stack type-A connector at rear I/O, USB 3.0 Gen1 on Front side
- HDD bays: External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
- Front: 120 x 25 mm x1 PWM Fan,Rear: 120 x 25 mm x1 PWM Fan
- 550/1200W Redundant Power Supply
- Optional : 500/1200W Single Power Supply



Processor/Cache		Drive bays	
Processor	4th/5th Gen Intel® Xeon Dual Processor	HDD Bays	External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
GPU		Power Supply	
GPU	2 x Dual-Slot PCIe GPU, RTX 4000/5000/6000 Ada	Power Supply	550/1200W Redundant Power Supply Optional : 500/1200W Single Power Supply
Expansion Slot		Cooling System	
PCI-Express	5 x16 PCIe5.0 , 1 x8 PCIe5.0 , 3 x8 MCIO PCIe5.0, 2 x M.2 2280 PCIe Gen4.0 x4 (Onboard)	Front	120 x 25 mm x1 PWM Fan
Integrated Onboard		Rear	120 x 25 mm x1 PWM Fan
SATA	SAS/SATA Storage : 2 x SATA3.0 (6 Gb/s) 7pin connectors, 1 x Slimline connector (up to 8 SATA ports)	Form Factor	
Front Panel		Form Factor	Tower/5U Rackmount
		Dimensions	
Front I/O Ports	1 x Power Button, 1 x Reset Button, 2 x USB 3.0, 1 x System Power LED Button	Dimensions	560 x 200 x 430 mm (22" x 7.9" x 16.9")
Rear I/O Ports	2 x 1000Base-T Ethernet Ports, 1 x 1000Base-T Dedicated Server Management Port, 2 x USB 3.1 Gen1 Type-A Port, 1 x DB-15 VGA connector, 1 x UID LED Button, 1 x External UID/switch button	Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com	