

Tyrone Camarero Specifications



Camarero ASDOTi-32

Key features

- Ultra Compact Form Factor
- Three Graphics Outputs (D-Sub/HDMI/DP)
- USB 3.1 Gen1 Type-C
- Room for two 2.5" HDDs/SSDs
- 1xM.2 Slot for WiFi+BT Module
- 1xm.2 SSD Slot (PCIe Gen3x4)
- Supports 2 x 2.5" HDDs or SSDs. HDD support type: 2.5" SATA hard drive
- 19V Power Adapter



Processor/Cache

Processor Supports 7th and 6th Generation Intel® Core™ i7/i5/i3/Pentium®/ Celeron® Processors (Socket 1151)

Chipset

Chipset Intel® H110

System Memory

Memory Capacity Supports DDR4 2400 MHz, 2 x SO-DIMM slots, Max. 32GB

Expansion Slots

PCI-Express 1 x M.2 Slot for WiFi + BT Module, 1 x M.2 SSD Slot (Supports type 2280 M.2 PCIe Gen3 x4)

LAN Intel® Gigabit I219V LAN

Add-on Options

Graphics Intel® HD Graphics

Audio Realtek ALC283

Front Panel

Front I/O Power Button, Power LED & HDD LED, 1xUSB 3.1 Gen1, 1xUSB 3.1 Gen1 (Type-C), 1xHEADPHONE WITH mic, 1xMIC-In

Rear I/O 1 x VGA, 1 x HDMI, 1 x DP, 1 x USB 3.1 Gen1, 1 x USB 2.0, 1 x LAN, 1 x DC-In Jack

Connectors 2 x USB 2.0 Headers, 1 x Internal Speaker Header (4-Pin), 1 x Front Panel Header, 1 x Chassis Intrusion (2-Pin)

Drive Bays

HDD bays Supports 2 x 2.5" HDDs or SSDs. HDD support type: 2.5" SATA hard drive

Power Supply

19V Power Adapter

Accessories

1x CD, 1x QIG, 1x Power Adaptor,

Form Factor

Ultra Compact Form Factor

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com