Tyrone Camarero Specifications

Camerero DI20037R-216R4T

Key features

- Supports Dual Intel® Xeon® processor E5-2600 product family •
- 24 Dimms DDR3 ECC UDIMM, RDIMM, LRDIMM up to 1600 speed ٠
- 4 x PCI-Express x8 Full-Height Full-length 2 x PCI-Express x8 Full-Height Half-Length •
- 4 x1 GbE •

-

- 16 x 2.5" SAS/SATA hot-plug •
- Redundant Power Supplies 2 x750W AC, Platinum Efficient •
- 2U with Rack Rails Included •





Processor/Cacne		Drive bays
Processor	Intel® Xeon® processors E5-2600 family	16 x 2.5" SAS/SATA hot-plug
Chipset		Power Supply
Chip set C600-A		Redundant Power Supplies 2 x750W AC, Platinum Efficient
System Memory		Form Factor
Memory Capacity	24 Dimms DDR3 ECC up to 1600 speed	2U with Rack Rails Included
Expansion Slots		
PCI-Express	4 x PCI-Express x8 Full-Height Full-length 2 x PCI-Express x8 Full-Height Half-Length	
Integrated On-Board		
8-port SAS 6Gbps RAID controller with Hardware RAID 0, 1, 10, 5 & 6 With 16-port SAS Expander (Intel RMS25CB080 + RES2CV240)		
Add-on Options		
Raid Op	otional	E : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com

o Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries

o Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners

