

Tyrone Camarero Specifications



Camarero DS20036W-14RT

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1.5TB ECC DDR3, up to 1866MHz; 24x DIMM sockets
- 1 PCI-E 3.0 (x8) Low-profile, 1 PCI-E 3.0 (x16) & 1 PCI-E 3.0 (x8) Full-height slots
- Intel i350 Dual port GbE & Intel X540 Dual port 10GBase-T Controllers
- 4x Hot-swap 3.5" SAS/SATA HDD Bays Connected to onboard storage controller
- 750/700W Redundant Power Supplies 80 Plus, Gold Level Certified



Processor/Cache

Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family

Chipset

Intel ® C602 Chipset

System Memory:

24x 240-pin DDR3 DIMM sockets Up to 1.5TB DDR3 ECC LRDIMM Up to 768GB DDR3 ECC Registered memory (RDIMM)

Expansion Slots:

1 PCI-E 3.0 (x8) Low-profile, 1 PCI-E 3.0 (x16) & 1 PCI-E 3.0 (x8) Full-height slots

Integrated On-Board

SAS SATA	SAS from C606 RAID 0, 1, 10 support Via Cable for SATA controller SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1
LAN	2x RJ45 10GBase-T ports 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port

Add-on Options

RAID card	Optional
Optical Drive	Optional

Front Panel :

LED Indicators: Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED, Universal Information (UID) LED
Switches: Power On/Off Button, System Reset Button, UID Button

Drive bays

HDD bays	4x Hot-swap 3.5" SAS/SATA HDD Bays Connected to onboard storage controller
Peripheral Bays	Slim DVD-ROM drive (optional)

Power Supply

750/700W Redundant Power Supplies 80 Plus, Gold Level Certified

Cooling System

6x 4cm Counter-rotating PWM fans

Form Factor

1U Rackmount
Width: 17.2" (437mm),
Height: 3.5" (89mm),
Depth: 25.5" (648mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com