

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

Camarero DS2003T26R

## Key features

Two hot-pluggable systems (nodes) in a 2U form factor. Each node supports the following:

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- 1x MicroLP PCI-E 3.0 x8 slot
- Intel® i350 Dual port Gigabit Ethernet
- 6x Hot-swap 3.5" SAS2/SATA3 HDD Bays
- LSI 2108 SAS2 Controller(BPN-ADP-SAS2-H6iR)
- 1280W Redundant Power Supplies ,Platinum Level



Processor/Cache	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
Chipset	
	Intel® C602 Chipset
System Memory	
Memory Capacity	16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM)
Expansion Slots	
PCI-Express	1x MicroLP PCI-E 3.0 x8 slot
Integrated On-Board	
SATA	SATA 2.0 & 3.0 with RAID 0, 1, 5, 10
SAS	LSI 2108 SAS (6Gbps) w/ Hardware RAID support RAID 0, 1, 5, 6, 10, 50, 60 support
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional
Optical Drive	None

Front Panel :	
LED Indicators	2x Network activity LEDs Universal Information (UID) LED
Switches	Power On/Off button System Reset button
Drive bays	
HDD bays	6x Hot-swap 3.5" SATA HDD trays
Power Supply	
	1280W Redundant Power Supplies, Platinum Level
Cooling System	
	4x 8cm heavy duty PWM fans with optimal fan speed control
Form Factor	
	2U Rackmount
Width	17.25" (438mm)
Height	3.47" (88mm)
Depth	28.5" (724mm)
<p><b>E : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	