

# Tyrone Camarero Specifications

**Tyrone**

## Camarero DS200T3G1-210RT

### Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 4x PCI-E 3.0 x16 slots (support GPU/Xeon Phi cards, opt.) 1x PCI-E 3.0 x8 (in x16) slot 1x PCI-E 2.0 x4 (in x16) slot
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® X540 10GBase-T Controller
- 10x Hot-swap 2.5" SATA Drive Bays
- 1800W Redundant Power Supplies 80Plus Platinum Level (94%+)
- 5x heavy duty cooling fans
- Smart server management tools
- Intel® Xeon Phi™ Support



<b>Processor/Cache</b>		<b>Front Panel :</b>	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	LED Indicators	Power LED/Hard drive activity LED /2x Network activity LEDs / System Overheat LED
		Switches	Power On/Off Button
<b>Chipset</b>		<b>Drive bays</b>	
Intel® C602 Chipset		HDD bays	10x 2.5" Hot-swap drive bays
		Peripheral Bays	None
<b>System Memory</b>		<b>Power Supply</b>	
Memory Capacity	8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered memory (RDIMM)	1800W Redundant Power Supplies 80Plus Platinum Level (94%+)	
<b>Expansion Slots</b>		<b>Cooling System</b>	
PCI-Express	4x PCI-E 3.0 x16 slots (support GPU/Xeon Phi cards, opt.) 1x PCI-E 3.0 x8 (in x16) slot 1x PCI-E 2.0 x4 (in x16) slot	5x 8cm heavy duty fans with optimal fan speed control	
<b>Integrated On-Board</b>		<b>Form Factor</b>	
SATA	SATA 2.0 & 3.0 with RAID 0, 1, 5, 10	2U Rackmount, Height – 3.5" (89mm), Width - 17.2" (437mm), Depth - 30.5" (775mm)	
LAN	2x RJ45 10GBase-T ports 1x RJ45 Dedicated IPMI LAN port		
<b>Add-on Options</b>		<b>E : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b>	
RAID Card	Optional	<b>For more/current product information, visit</b>	
Optical Drive	None	<b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b>	