

Tyrone Camarero Specifications

Camarero DS200T6R-14+

Tyrone[®]

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- 1x PCI-E 3.0 x8 Full-height, Full-length Expansion slot
- Intel® i350 Dual port Gigabit Ethernet
- 4x 3.5" Hot-swap SATA HDD Bays
- **600W High-efficiency power supply Gold Level Certified**



Processor/Cache		Front Panel :	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	LED Indicators	Power status LED ,HDD activity LED , 2x Network activity LEDs Universal , Information (UID) LED
		Switches	Power On/Off button System Reset button
Chipset		Drive bays	
	Intel® C602J Chipset	HDD bays	4x 3.5" Hot-swap 3.5" SATA HDD trays
System Memory		Power Supply	
Memory Capacity	16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM)		600W High-efficiency power supply Gold Level Certified
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 x8 Full-height, Full-length		2x blower fans ,1x 40 x 28mm 13K RPM 4-pin fan
Integrated On-Board		Form Factor	
SATA	Via Cable for SATA controller.SATA 2.0 (3Gbps) & 3.0 (6Gbps) with SATA 2.0 (3Gbps) & 3.0 (6Gbps) with RAID 0, 1, 5, 10		1U Rackmount
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Width	17.2" (437mm),
		Height	1.7" (43mm),
		Depth	25.6" (650mm)
Add-on Options		Email : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com	
RAID Card	Optional		
Optical Drive	None		