

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS200T6R-14



Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- 1x PCI-E 3.0 x16 FHHL Expansion slot
- Intel® i350 Dual port Gigabit
- 4x 3.5" Hot-swap SATA HDD Bays
- 440W-480W High-efficiency Power Supply; Platinum Level



Processor/Cache

Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family

Chipset

Intel® C602 Chipset

System Memory

8x 240-pin DDR3 DIMM slots. Up to 512GB DDR3 ECC LRDIMM. Up to 256GB DDR3 ECC Registered memory (RDIMM). Up to 64GB DDR3 ECC Un-Buffered memory (UDIMM)

Expansion Slots

1x PCI-E 3.0 x16 FHHL Expansion slot

Integrated On-Board

SATA: Via Cable for SATA controller SATA 2.0 (3Gbps) & 3.0 (6Gbps) with RAID 0, 1, 5, 10

LAN: 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port

Add-on Options

Raid card Optional

Optical Drive :None

Front Panel :

LED Indicators:Power LED Hard drive HDD activity LED 2x Network activity LEDs Universal Information (UID) LED
Switches:Power On/Off button System Reset button , UID button

Drive bays

HDD Bays 4x 3.5" Hot-swap 3.5" SATA HDD trays
Peripheral Drive : None

Power Supply

440W-480W High-efficiency Power Supply; Platinum Level

Cooling System

2x 10cm PWM blower fans

Form Factor

1U Rackmount

Width 17.2" (437mm)

Height 1.7" (43mm)

Depth 25.6" (650mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com