

Tyrone Camarero Specifications

Tyrone®

Camarero DS200T6R-48RX



Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- Expansion slots: 3 (x16) PCI-E 3.0 and 3 (x8) PCI-E 3.0 slots
- 2x Gigabit Ethernet LAN ports; Intel® i350 Dual port GbE Controller
- 2x SATA3, 8x SATA2 ports
- 8x Hot-swap 3.5" HDD Bays
- 920W Redundant Power Supplies 80PLUS, Platinum Level Certified
- Tower or Rackmount

Processor/Cache

Processor Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family

Chipset

Intel® C602 Chipset

System Memory

Memory Capacity 16x 240-pin DDR3 DIMM sockets
Up to 1TB DDR3 ECC LRDIMM
Up to 512GB DDR3 ECC Registered memory (RDIMM)

Expansion Slots

PCI-Express 3 (x16) PCI-E 3.0 slots 3 (x8) PCI-E 3.0 slots"

Integrated On-Board

SATA SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1, 5, 10
"LAN 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port"

Add-on Options

RAID Optional

Optical Drive Optional"

Front Panel :

LED Indicators Power LED/ Hard drive activity LED
/2x Network activity LEDs
/ System Overheat LED
Switches Power On/Off Button

Drive bays

HDD Bays 8x Hot-swap 3.5" SAS/SATA Drive Trays
Peripheral Bays 2x 5.25" Peripheral Drive Bays 1x 5.25" Bay that fits 3.5" bay devices

Power Supply

920W Redundant Power Supplies 80PLUS, Platinum Level Certified"

Cooling System

3x 5000 RPM Hot-swap PWM Cooling Fans 2x 5000 RPM Hot-swap Rear Exhaust PWM Fans

Form Factor

4U Rackmount / tower, Height 17.2" (437mm), Width 7.0" (178mm), Depth 25.5" (648mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com