

Tyrone Camarero Specifications

Tyrone

Camarero DS200T6W-216R

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- 4x PCI-E 3.0 x8 slots (2x Full-height Full-length, 2x Full-height Half-length)
- Intel® i350 Dual port Gigabit Ethernet Controller; 2x LAN ports
- 16x Hot-swap 2.5" SAS/SATA HDD bays for Customizable Storage
- 740W Redundant power supplies Platinum Level (94%+)



Processor/Cache		Front Panel :	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	LED Indicators	Power LED/Hard drive activity LED /2x Network activity LEDs /System Overheat LED
		Switches	Power On/Off Button
Chipset		Drive bays	
Intel® C602 Chipset		HDD bays	16x Hot-swap 2.5" SAS / SATA HDD trays
		Peripheral Bays	Slim DVD-ROM drive (optional)
System Memory		Power Supply	
Memory Capacity	16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM)	740W Redundant power supplies Platinum Level (94%+)	
Expansion Slots		Cooling System	
PCI-Express	4x PCI-E 3.0 x8 slots (2x Full-height Full-length, 2x Full-height Half-length)	3x 80mm 7,000 RPM 4-pin PWM fans	
Integrated On-Board		Form Factor	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10, SATA 3.0 6Gbps with RAID 0, 1, 5, 10	2U Rackmount, Width 17.2" (437mm), Height 3.5" (89mm) Depth 24.8" (630mm)	
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port		
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	
RAID	Optional		
Optical Drive	Optional		

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/or other Countries
 Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners