Tyrone Camarero Specifications

Camarero DS200TR-12R

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Intel® C602 chipset
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 1x PCI-E 3.0 x16 FHHL Expansion slot
- Intel® i350 Dual port Gigabit Ethernet
- 2x 3.5" Hot-swap SATA HDD Bays
- 2x 10cm PWM blower fans
- 500W Redundant Power Supplies Platinum Level (94%+)



Tyrone



Processor/Cache		Front Panel	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600	Buttons	Power On/Off button, System Reset buttor
	v2 family	LED	Power status LED HDD activity LED 2x Network activity LEDs Universal Information (UID) LED
Chipset		Drive Bays	
	Intel® C602 chipset	2x 3.5" Hot-swap SATA HDD trays	
System Memory		Power Supply	
Memory Capacity	Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets	500W Redundant Power Supplies, Platinum Level (94%+)	
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 x16 Full-height, Half-length	2x 10cm PWM blower fans	
Integrated On-Board		Form Factor	
SATA	Via Cable for SATA controller, SATA 3.0 (6Gbps) with RAID 0, 1	1U Rackmount Width	
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Height Depth	17.2" (437mm) 1.7" (43mm) 25.6" (650mm)
Add-on Options			
		En	nail : info@tyronesystems.com
Raid Card	Optional		/current product information, visit www.tyronesystems.com

O Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries

O Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners