Tyrone Camarero Specifications

Tyrone

Camerero DS2B0T6R-14

Key features

- Dual socket B2 (LGA 1356) supports Intel® Xeon® processor E5-2400 v2
- Up to 192GB DDR3 1600MHz ECC R/LRDIMM; 6x DIMM sockets
- 1 PCI-E 3.0 x16 Expansion slot (FHFL)
- Intel® 82574L GbE LAN, 2 ports
- 4x Hot-swap 3.5" SATA HDD Bays
- 440W High-efficiency Power Supply Platinum Level (94%+) power supply
- 1U Short Depth 19.8" (503mm)







Processor/Cache

Dual socket B2 (LGA 1356) Processor supports Intel® Xeon® processor E5-2400 v2

Chipset

Intel® C602 Chipset

System Memory

Memory Capacity 6x 240-pin DDR3 DIMM sockets

Supports up to 192 GB DDR3 ECC

Expansion Slots

PCI-Express 1x PCI-E 3.0 x16 Full-height

Half-length

Integrated On-Board

SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA

SATA 3.0 6Gbps with RAID 0, 1, 5, 10

LAN LAN:2 RJ45 Gigabit Ethernet LAN

ports 1 RJ45 Dedicated IPMI LAN port

Add-on Options

RAID Card Optional Optical Drive Optional

Front Panel:

Power status LED,HDD activity LED,2x Network activity LEDs,Universal Information (UID) LED **LED Indicators**

Switches Power On/Off button, System Reset

button, UID button

Drive bays

HDD bays 4x Hot-swap 3.5" SATA HDD trays

Peripheral Bays Optional

Power Supply

440W High-efficiency Power Supply Platinum Level (94%+) power supply

Cooling System

4x 4cm 12,500 RPM PWM fans

Form Factor

1U Rackmount

Width 17.2" (437mm), Height 1.7" (43mm), Depth 19.8" (503mm)

> Email: info@tyronesystems.com For more/current product information, visit www.tyronesystems.com