

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS2B0TR- 316R

Key features

- Dual socket B2 (LGA 1356) supports Intel® Xeon® processor E5-2400 v2
- Intel® C602 chipset
- Up to 384GB DDR3 1600MHz LRDIMM / 192GB RDIMM; 6x DIMM slots
- Expansion slots: 1 PCI 32, 1 PCI-E 3.0 x16, 1 PCI-E 3.0 x4 (in x8) 3 PCI-E 3.0 x8 (1 allows a x16 card)
- Intel® 82574L Dual port GbE LAN
- 8x SATA2 and 2x SATA3 ports
- 4x USB 3.0 and 10x USB 2.0 ports
- 3x 80mm Hot-swap PWM Fans. 2x 80mm Rear-exhaust Fans
- 500W Redundant Power Supplies Platinum Level (94%)



Processor/Cache		Front Panel	
Processor	Dual socket B2 (LGA 1356) supports Intel® Xeon® processor E5-2400 v2	LED	Power LED Hard drive activity LED, 2x Network activity LEDs, System Overheat LED, Power fail LED
		Switches	Power On/Off Button, System Reset Button
Chipset		Drive Bays	
	Intel® C602 chipset	HDD bays	16x 3.5" SAS / SATA Hot-swap drive trays SAS or enterprise SATA HDD only recommended
System Memory		Power Supply	
Memory Capacity	6x 240-pin DDR3 DIMM sockets Up to 192GB DDR3 ECC Registered memory (RDIMM)		500W Redundant Power Supplies Platinum Level (94%)
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 x16, 3x PCI-E 3.0 x8 (1 allows a x16 card), 1x PCI-E 3.0 x4 (in x8), 1x PCI-32		3x 80mm Hot-swap PWM Fans 2x 80mm Rear-exhaust Fans
Integrated On-Board		Form Factor	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10, SATA 3.0 6Gbps with RAID 0, 1, 5, 10	3U Rackmount	
LAN	2 RJ45 Gigabit Ethernet LAN ports	Dimensions	Height – 5.2" (132mm) Width - 17.2" (437mm) Depth - 25.6" (650mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid card	Optional		
Optical Drive	Optional		