

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS2B0TR-48R

Key features

- Dual socket B2 (LGA 1356) supports Intel® Xeon® processor E5-2400 v2
- Intel® C602 chipset
- Up to 384GB DDR3 1600MHz LRDIMM / 192GB RDIMM; 6x DIMM slots
- 1 PCI, 3 PCI-E 3.0 x8 1 PCI-E 3.0 x16, 1 PCI-E 3.0 x4 (in x8)
- Intel® 82574L GbE LAN, 2 ports
- 8x SATA2 and 2x SATA3 ports
- 8 x 3.5" SAS/SATA Hot-swappable Drive Bays
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 7x USB 2.0 ports (2 rear, 4 via header + 1 Type A)
- 3x 5000 RPM Hot-swap PWM Cooling Fans 2x 5000 RPM Hot-swap Rear Exhaust PWM Fans
- Rack mount / Tower Convertible
- 800W Redundant High-efficiency Power Supplies



Processor/Cache		Front Panel	
Processor	Dual socket B2 (LGA 1356) supports Intel® Xeon® processor E5-2400 v2	LED Indicators	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Information LED, Power Fail LED
Chipset	Intel® C602 chipset	Buttons	Power On/Off button System Reset button
System Memory		Drive Bays	
Memory Capacity	6x 240-pin DDR3 DIMM slots, Up to 384GB DDR3 ECC LRDIMM	HDD bays	8 x 3.5" SAS/SATA Hot-swappable Drive Bays.
Expansion Slots		Peripheral Bays	3x 5.25" Peripheral Drive Bay
PCI-Express	1x PCI-E 3.0 x16 3x PCI-E 3.0 x8 1x PCI-E 3.0 x4 (in x8) 1x PCI-32	Power Supply	
Integrated On-Board		800W Redundant High-efficiency Power Supplies	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1, 5, 10	Cooling System	
LAN	LAN2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port	3x 5000 RPM Hot-swap PWM Cooling Fans 2x 5000 RPM Hot-swap Rear Exhaust PWM Fans	
Add-on Options		Form Factor	
Raid	Optional	Form Factor	4U/Tower
Optical Drive	Optional	Width:7.0" (178 mm), Height: 17.8" (452mm) Depth:25.5" (648mm)	
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	