Tyrone Camarero Specifications

Camarero DS3007E1-212RL

Key features

Pro Pro

Chi

Syst

Exp

Inte

Add

- Dual socket R3 (LGA 2011) supports Intel[®] Xeon[®] processor E5-2600 v4⁺/ v3 family; UPI up to 9.6GT/s
- Intel[®] C612 chipset
- Up to 1TB ECC 3DS LRDIMM , up to DDR4- 2400⁺MHz ; 8x DIMM slots
- 1 PCI-E 3.0 x16, 2 PCI-E 3.0 x8
- Intel[®] i210 Dual GbE LAN ports
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 8 SAS3 (12Gbps) via Broadcom[®] 3108; HW,RAID 0, 1, 5, 6, 10, 50, 60 SuperCap Option support
- 6 SATA3 (6Gbps) via C232; RAID 0, 1, 5, 10
- 4 USB 3.0 (2 rear, 2 via header)3 USB 2.0 (2 via header, 1 Type A)
- 12 x 3.5" hot-swap SAS/SATA drive bay with SES3, optional 2 x 2.5" hot-swap drive bay
- 3 x 8cm high-performance PWM fan(s).
- 920W Redundant Platinum Super Quiet power supply W/PMbus

Tyrone





supply W/PMbus

Processor/Cache		Front Panel		
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4†/ v3 family; UPI up to 9.6GT/s	LEDs	2 Network Activity LEDs, Fan Fail/System Over Heat LED, HDD activity LED, Power Status LED, Unit Identification (UID) LED	
Chipset		Buttons	Power On/Off button,System Reset button	
Chipset	Intel [®] C612 chipset	Drive Bays		
System Memory		Drive Bays	12 x 3.5" hot-swap SAS/SATA drive bay	
Memory Capacity	Up to 1TB† ECC 3DS LRDIMM , up to DDR4- 2400†MHz ; 8x DIMM slots		with SES3, optional 2 x 2.5" hot-swap drive bay	
Expansion Slots		Power Supply	Power Supply	
PCI-Express	1 PCI-E 3.0 x16, 2 PCI-E 3.0 x8	920W Redundant Pl	920W Redundant Platinum Super Quiet power supply W/PMbu	
ntegrated On-Board		Cooling System		
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	3 x 8cm high-perfo	3 x 8cm high-performance PWM fan(s)	
SAS	Broadcom 3108 SAS3 (12Gbps) controller;2GB cache with SuperCap	Form Factor		
	backup option; HW RAID 0, 1, 5, 6, 10, 50, 60 ,Supports up to 16 devices as default, more HDD devices support is also available as an option	Form Factor Height: Width:	2U Rackmount 3.5" (89 mm), 17.2" (437 mm),	
LAN	2x RJ45 Gigabit Ethernet LAN ports,	Depth:	25.5" (647 mm))	
1x RJ45 Dedicated IPMI LAN port Add-on Options		Email : info@tyronesystems.com		
Optical Drive	None	For more/current product information, visit www.tyronesystems.com		

O Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries
O Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners