

Tyrone Camarero Specifications



Camarero DS300TGX-14RT

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family
- Intel® C612 chipset
- Up to 2TB ECC 3DS LRDIMM , up to DDR4- 2400MHz ; 16x DIMM slots
- 3 PCI-E 3.0 x16 slots, 1 PCI-E 3.0 x8 Low-profile slot
- 2 10GBase-T LAN via Intel X540
- 2x 2.5" Hot-swap drive bays, 2x 2.5" internal drive bays
- 8x 4cm heavy duty counter-rotating fans with air shroud & optimal fan speed control
- 2000W Redundant Power Supplies Titanium Level (96%)



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family	LED	Power status LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED / Fan fail LED /UID LED
Chipset	Intel® C612 chipset	Buttons	Power On/Off button, System Reset button
System Memory		Drive Bays	
Memory Capacity	16x 288-pin DDR4 DIMM slots, Up to 2TB ECC 3DS LRDIMM, 1TB ECC RDIMM	Hotswap	2x 2.5" Hot-swap drive bays
Expansion Slots		Fixed	2x 2.5" internal drive bays
PCI-Express	3 PCI-E 3.0 x16 slots, 1 PCI-E 3.0 x8 low-profile slot	Power Supply	
Integrated On-Board		2000W Redundant Power Supplies Titanium Level (96%)	
SATA	SATA3 (6Gbps) with RAID 0, 1, 5, 10	Cooling System	
LAN	2 RJ45 10GBase-TEthernet ports, 1 RJ45 Dedicated IPMI LAN port	8x 4cm heavy duty counter-rotating fans with air shroud & optimal fan speed control	
Add-on Options		Form Factor	
Raid	Optional	Form Factor	1U Rackmount
Optical Drive	Optional	Height	: 1.7"(43mm),
		Width	: 17.2"(437mm),
		Depth	: 35.2"(894mm),
			39.3"(997mm) with rails
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	