Tyrone Camarero Specifications

Tyrone

Camarero DS300TR-12RT

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/v3 family
- Intel® C612 Express chipset
- Up to 2TB ECC 3DS LRDIMM, up to DDR4- 2400MHz; 16x DIMM slots
- 2x PCI-E 3.0 x16 (FHHL) slots
- 2x 2.5" Fixed drive bays w/ bracket
- Intel® X540 Dual port 10GBase-T
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- I/O ports: 2x SuperDOM, 1x VGA, 1x COM, 2x USB 3.0, 4x USB 2.0
- 400W Redundant Power Supplies Gold Level; BBP option







Processor/Cache

Dual socket R3 (LGA 2011) supports Intel® Processor

Xeon® processor E5-2600v4/ v3 family

Chipset

Intel® C612 Express chipset Chipset

System Memory

Memory Capacity 16x 288-pin DDR4 DIMM slots, Up to 2TB

ECC 3DS LRDIMM, 512 ECC RDIMM

Expansion Slots

PCI-Express 2x PCI-E 3.0 x16 Full-height, Half-length

Integrated On-Board

SATA SATA3 (6Gbps); RAID 0, 1, 5, 10

LAN 2x RJ45 10GBase-T ports, 1x RJ45

Dedicated IPMI LAN port

Add-on Options

Raid Optional

Optical Drive None **Front Panel**

LED Indicators Power status LED, Hard drive activity LED,

2x Network activity LEDs, system

Overheat LED

Buttons Power On/Off button, System Reset button

Drive Bays

HDD Bays (Internal) 2x 2.5" Fixed drive bays with bracket

Power Supply

400W Redundant Power Supplies Gold Level; BBP option

Cooling System

4x 40x56mm PWM fan; 2x fans for AOC cooling

Form Factor

Form Factor 1U Rackmount

Width: 17.2"(437 mm), Height: 1.7" (43mm), 16.9" (429mm) Depth:

Email: info@tyronesystems.com

For more/current product information, visit www.tyronesystems.com