Tyrone Camarero Specifications

Camarero DS300TR-48L Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family; QPI up to 9.6GT/s
- Intel® C612 chipset
- Up to 2TB ECC 3DS LRDIMM, up to DDR4- 2400MHz; 16x DIMM slots
- 3 PCI-E 3.0 x16 and 3 PCI-E 3.0 x8
- Intel® i350 Dual port GbE LAN
- 10x SATA3 (6Gbps); RAID 0, 1, 5, 10
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 5x USB 3.0 (2 rear, 2 via header, 1 Type A), 6x USB 2.0 (2 rear, 4 via header)
- 8x 3.5" SAS/SATA Backplane for Hot-Swappable Drives
- 2x 8cm PWM Fans & 1x 9cm Rear PWM Fan
- 1200W Platinum Level Certified High-Efficiency Power Supply







	ce			

Processor Dual socket R3 (LGA 2011) supports

Intel® Xeon® processor E5-2600 v4/ v3

family; QPI up to 9.6GT/s

Chipset

Chipset Intel® C612 chipset

System Memory

Memory Capacity 16x 288-pin DDR4 DIMM slots, Up to

2TB+ ECC 3DS LRDIMM, 1TB ECC RDIMM

Expansion Slots

PCI-Express 3 PCI-E 3.0 x16, 3 PCI-E 3.0 x8

Integrated On-Board

SATA SATA3 (6Gbps); RAID 0, 1, 5, 10

LAN 2x RJ45 Gigabit Ethernet LAN ports,

1x RJ45 Dedicated IPMI LAN port

Add-on Options

Raid Optional

Optical Drive Optional

Front Panel

LEDs 2 Network Activity LEDs,Fan Fail/System

Over Heat LED,HDD activity LED,Power Status LED, Unit Identification (UID) LED

Buttons Power On/Off button System Reset button

Drive Bays

HDD bays 8 x 3.5" hot-swap SAS/SATA drive bay

with SGPIO

Peripheral Bays 2 x standard 5.25" drive bay, 90 degree

rotatable drive cage

Power Supply

1200W Platinum Level Certified High-Efficiency Power Supply

Cooling System

2x 8cm PWM Fans & 1x 9cm Rear PWM Fan

Form Factor

Form Factor 4U Rackmount/Tower Height : 17.8" (452 mm),

Width : 7" (178 mm), Depth : 25.5" (647 mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com