# **Tyrone Camarero Specifications**

# Camarero DSA700TR-212R4

### Key features

- Virtualization, Hyperconverge Storage, Cloud Computing, High End Enterprise Server, Flexible Networking Options
- Dual AMD EPYC™ 7001/7002\* series Processors (Up to 225W and board revision 2.x required),
   Up to 32 Cores, Up to 64 Cores (Board revision 2.x required)
- System on Chip (SoC)
- Up to 4TB Registered ECC DDR4 2666MHz SDRAM in 32 DIMMs
- 1 PCI-E 3.0 x16 slot (FH, 10.5" L) , 5 PCI-E 3.0 x8 slots (FH, 9.5" L) , 1 PCI-E 3.0 x8 slot (LP) , 1 PCI-E 3.0 x8 (internal LP).
- Integrated IPMI 2.0 + KVM with dedicated LAN
- 3 USB 3.0 ports (2 rear + 1 Type A), VGA, Serial port
- Quad Gigabit LAN ports via Intel i350AM4
- 12 hot-swap 3.5" Drive Bays: 12 SATA3 by default or 8 SATA3 + NVMe (optional supported) or 12 SAS3 (SAS Add-on card is optional)
- · 4 heavy-duty PWM fans with optimal fan speed control
- 1600W Redundant Power Supplies Titanium Level (96%+)
- Optional Supports 2GPU.





# Processor/Cache

Processor Dual AMD EPYC™ 7001/7002\* series

Processors (Up to 225W and board revision 2.x required), Up to 32 Cores, Up to 64 Cores (Board revision 2.x required)

#### Chipset

Chipset System on Chip (SoC)

#### System Memory

Memory Capacity 32 DIMM sockets, Supports up to 4TB

Registered ECC DDR4 2666MHz SDRAM

in 32 DIMMs

## **Expansion Slots**

PCI-Express 1 PCI-E 3.0 x16 slot (FH, 10.5" L), 5 PCI-E

3.0 x8 slots (FH, 9.5" L), 1 PCI-E

3.0 x8 slot (LP) , 1 PCI-E 3.0 x8 (internal LP)

#### Integrated On-Board

SATA SATA3 (6 Gbps)

LAN Quad Gigabit LAN ports, 1 RJ45 Dedicated

IPMI LAN port

## **Add-on Options**

Raid Card Optional

Optical Drive None

Ports 3 USB 3.0 ports (2 rear + 1 Type A),

VGA, Serial port

Front Panel

LED Indicators Power LED, Hard drive activity LED, 2x Network

activity LEDs, System Overheat LED /

Fan fail LED / UID LED

Buttons Power On/Off button,

System Reset button

**Drive Bays** 

HDD bays 12 hot-swap 3.5" Drive Bays: 12 SATA3 by

default or 8 SATA3 + NVMe (optional

supported) or 12 SAS3 (SAS Add-on card is optional)

**Power Supply** 

1600W Redundant Power Supplies Titanium Level (96%+)

Cooling System

4 heavy-duty PWM fans with optimal fan speed control

Form Factor

Form Factor 2U Rackmount

Width: 17.2" (437mm), Height: 3.5" (89mm), Depth: 28.46" (723mm)

As per Bureau of Indian Standards Tyrone Camarero Model Series DS4C0VWXY-ZZ AMD the AMD logo Inside are trademarks of Advanced Micro Devices in US and /Or Other countries

AMD I HE AMD logs lessee are trademarks of Advanced Micro Devices in US and for Other Countries

Specifications subject to change without notice. Picture used for representation purpose on and the actual product may differ in looks. All other brands and names are the property of their respective owners