Tyrone Camarero Specifications

Camarero DSA70TN-54TR

Key features

- Dual AMD EPYC™ 7001/7002* series Processors (*Board revision 2.x required) Socket SP3,
 Up to 240W TDP Cores :Up to 32 Cores, Up to 64 Cores (Board revision 2.x required)
- System on Chip
- 16 DIMM sockets, Supports up to 2TB Registered ECC DDR4 2666MHz SDRAM,
 Supports up to 4TB Registered ECC DDR4 3200MHz SDRAM (Board revision 2.x required), 8-channel
 memory bus
- 3 PCI-E 3.0 x8, 2 PCI-E 3.0 x16, M.2, Interface: 1 SATA/PCI-E 3.0 x2 (Platform with EPYC 7002 processor only supports PCI-E type M.2 module), Form factor: 2280, 22110, Key: M-key
- 10 SATA3, 1 M.2, 2 SATA DOM
- Dual 10GBase-T LAN Ports
- ASPEED AST2500 BMC graphics
- Up to 2 USB 3.0 ports, Up to 4 USB 2.0 ports
- 8 4-pin PWM Fan & Speed control
- External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x 5
- Front:120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan
- 550 / 1200W Redundant power supply ,80 Plus platinum



Processor/Cache

Processor Dual AMD EPYC™ 7001/7002* series Processors

(*Board revision 2.x required) Socket SP3, Up to 240W TDP

Cores :Up to 32 Cores, Up to 64 Cores

(Board revision 2.x required)

Chipset

Chipset System on Chip

System Memory

Memory Capacity

16 DIMM sockets, Supports up to 2TB Registered ECC DDR4 2666MHz SDRAM, Supports up to 4TB Registered ECC DDR4 3200MHz SDRAM (Board revision 2.x required), 8-channel

memory bus

Expansion Slots

PCI-Express

3 PCI-E 3.0 x8, 2 PCI-E 3.0 x16, M.2, Interface: 1 SATA/PCI-E 3.0 x2

(Platform with EPYC 7002 processor only supports PCI-E type M.2 module),

Form factor: 2280, 22110, Key: M-key

Integrated Onboard

SATA 10

10 SATA3 (6 Gbps) ports

LAN

2 RJ45 10GBase-T ports, 1 RJ45 Dedicated IPMI

LAN port

Add-on Options

Raid Card:

Optional

Optical Drive:

None

Front Panel

Front Panel

Front Control Panel Power Switch, System Reset

Buttons

Power On/Off button

Drive Bays

HDD Bays

External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x 5

Power Supply

550 / 1200W Redundant power supply ,80 Plus platinum

Cooling System

Front:120 x 25 mm x1 PWM Fan,

Rear: 120 x 25 mm x1 PWM Fan

Form Factor

Form Factor

5U Rackmount/tower/Convertable

Dimensions:

560 x 200 x 430 mm (22"" x 7.9"" x 16.9"")

Email: info@tyronesystems.com For more/current product information, visit www.tyronesystems.com

AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners