

Tyrone Camarero Specifications



Camarero ISNOTI-2

Key features

- Intel® Core TM i7-7567U Processor (3.5 GHz to 4.0 GHz Turbo, Dual Core 4 MB cache, 28W TDP)
- Intel® HD Graphics 650
- Two DDR4 SO-DIMM Sockets (upto 32 GB 2133 MHz)
- 1x SATA port for connection to 2.5" HDD or SSD
- M.2 slot with flexible support for a 42 or 80 mm M.2 SSD
- Intel @ Optane TM Memory ready
- Intel® Dual Band Wireless-AC 8265 and Bluetooth 4.2
- BackPanel DC Power connector (12-19V)
- One full-size HDMI 2.0 display port supporting 8 channel audio (7.1 surround sound)
- Intel® Gigabit LAN
- Four USB 3.0 ports
- One Thunderbolt™ 3 port with support for USB 3.1 gen 2, Display Port 1.2 and 40 Gb/s Thunderbolt
- Kensington lock support
- Micro SD Card slot
- 19V wall-mount AC-DC Power Adapter



Processor/Cache

Processor	Intel® Core TM i7-7567U Processor (3.5 GHz to 4.0 GHz Turbo, Dual Core 4 MB cache, 28W TDP)
-----------	---

Chipset

Chipset	Intel Integrated Chipset
---------	--------------------------

System Memory

Memory Capacity	Two DDR4 SO-DIMM Sockets (upto 32 GB 2133 MHz)
-----------------	---

Expansion Slots

PCI-Express	1x PCIe x4 for M.2
USB 3.0	4 (2 Front, 2 Rear)

Onboard Controllers

Graphics	Intel® HD Graphics 650
Audio	Upto 7.1 surround audio via HDMI, Headphone/Microphone jack on the front-panel. Dual array microphones on the front panel
LAN	Intel® Gigabit I219V LAN

Front Panel

LED Indicators	Reset, HDD LED, Power LEDs, Power on/off
Buttons	Front Panel power button

Drive Bays

HDD bays	1x M.2 and 1x 2.5" Drive
----------	--------------------------

Power Supply

19V AC-DC Power Adapter

Form Factor

Ultra Compact Form Factor (101.6mm x 101.6mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com