

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

## Camerero: MDI300A2N-224

### Key Feature

- Supports Dual Intel Xeon 6<sup>th</sup> Gen 6700E/6500P/6700P series Processors
- Supports 16+16 DDR5 RDIMM Expandable Memory
- 4 x16 PCIe 5.0 Expansion Slots
- Latest AST2600 BMC Controller
- Support 24 x 2.5" U.2 NVMe Hot Swappable Bays
- Supports 2 x PCIe 5.0 x4 E1.S Drives
- 80+ Titanium CRPS Power Supply
- Enhanced Security with TPM 2.0, ROT and local BMC logs storage option
- Dual BIOS and dual BMC



Processor/Cache		Indicators	
Processor	Dual Intel Xeon 6 <sup>th</sup> Gen 6700E/6500P/6700P series Processors of TDP Upto 350W (FCLGA 4710)	Indicators	1 x Power LED Button (Rear) 1 x UID LED Button (Rear) 1 x Status LEDs: Green/Red (Rear) 1 x System Power LED Button (Front) 1 x UID LED Button (Front) 1 x Reset Button (Front) 4 x Status LEDs: Fault/LAN/M.2 (Front)
System Memory		Security	
Memory Capacity	Supports 16+16 DDR5 Expandable Memory, Max Frequency : RDIMM : 6400MHz(1DPC), 5200MT/s(2DPC) MRDIMM : 8000MT/s(1DPC Only)	Security	Chassis Intrusion TPM 2.0 ROT (Optional)
Expansion Slot		Power Supply	
PCI-Express	3 x16 PCIe5.0 FHFL (Supports 2 x DW GPUs of TDP upto 400W) 1 x PCIe 5.0 x16 OCP 3.0 NIC	Power Supply	2700W 80+ CRPS Titanium Certified
Drive bays		Form Factor	
HDD Bays	24 x 2.5" PCIe 5.0 NVMe Hot Swappable Drives 2 x PCIe 5.0 x4 E1.S Hot Swappable Drives 2 x 2280/22110 PCIe5.0 x2 NVMe M.2 Drives	Form Factor	2U Rackmount
Ports		Dimension	
Ports	1 x USB 3.0 Type-A Port (Front) 1 x USB 2.0 Type-A Port (Front) 1 x 1000Base-T Dedicated Server Management Port (Rear) 1 x COM USB Type A port (Rear) 1 x USB 2.0 Type-A Port (Rear) 1 x Mini Display port (Rear)	Dimension	438mm(W) x 87mm(H) x 764mm(D)
		Email : <a href="mailto:Info@tyronesystems.com">Info@tyronesystems.com</a> For more/current product information, Visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a>	