

Tyrone Camarero Specifications

Tyrone[®]

Camarero QA600T3R-26R



Key features

- Four AMD Opteron™ 6000 series (6300P* ready) processors (Socket G34) 16/12/8/4-Core ready; HT3.0 Link support
- Up to 1TB DDR3 1600MHz ECC Registered DIMM; 32x DIMM sockets
- 2x PCI -e Gen 2.0 x16 slot, 1x PCI -e Gen 2.0 x8 slot, 1x UIO or x8 slot
- Dual-port GbE LAN Controller, 4x USB 2.0 ports, 1x dedicated LAN for system management (IPMI 2.0)
- 6x Hot-swap SATA Drive Bays
- 1400W High-efficiency Redundant Power Supplies 80Plus Gold Certified
- 6x 4-pin PWM fans with optimal fan speed control

Processor/Cache		Front Panel :	
Processor	Four AMD Opteron™ 6000 series (6300P* ready) processors (Socket G34) 16/12/8/4-Core ready; HT3.0 Link support	LEDs	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED, Power fail LED
		Buttons	Power On/Off button, System Reset button
Chipset		Drive bays	
SR5690/SR5670/SP5100		HDD bays	6x 3.5" SATA Hot-swap drive trays Enterprise SATA HDD only recommended
		peripheral bays	none
System Memory		Power Supply	
Memory Capacity	Thirty-Two DIMM sockets Up to 1TB DDR3 1600MHz ECC Registered DIMM; 32x DIMM sockets	1400W High-efficiency Redundant Power Supplies 80Plus Gold Certified	
Expansion Slots		Cooling System	
PCI-Express 2x PCI-e 2.0 x16 2x PCI-e 2.0 x8 1x UIO slot		6x 80mm 6500 RPM fans	
Integrated On-Board		Form Factor	
SATA	AMD SP5100 (RAID 0, 1, 10)	2U Rackmount, Height -3.5" (89mm), Width - 17.2" (437mm), Depth - 27.9" (709mm)	
LAN	2 RJ45 LAN ports 1 RJ45 Dedicated LAN supports IPMI		
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	
RAID	Optional		
Optical Drive	None		