

Tyrone Camarero Specifications



Camarero QS300TN-224R4

Key features



48 DDR4 DIMM Slots, up to 6TB, Up to 11 PCI-E 3.0 slots, 4 Hot-Swap NVMe Bays support via optional NVMe AOC, Flexible Connectivity Options

- Quad socket R3 (LGA 2011) supports Intel® Xeon® processor E5-4600 v4/v3 family
- Intel®C612 chipset
- Up to 6TB 3DS LRDIMM, up to DDR4-2400MHz; 48 DIMM slots
- 9 PCI-E 3.0 x8 slots, 2 PCI-E 3.0 x16 slots
- 4 GbE + 1 dedicated IPMI LAN ports
- 24 Hot-swap 2.5" Drive Bays: 4 Hybrid ports with NVMe support via extra AOC
- 4x 8cm heavy duty fans
- 1000W High efficiency (96%) Redundant PSU; Titanium Level



Processor/Cache		Front Panel	
Processor	Quad socket R3 (LGA 2011) supports Intel® Xeon® processor E5-4600 v4/v3 family	LED Indicators	Power status LED, HDD activity LED, Network activity LEDs, System information (overheat/UID) LED
Buttons		Buttons	Power On/Off button, System Reset button
Chipset		Drive Bays	
Chipset	Intel®C612 chipset	HDD Bays	24x 2.5" Hot-swap Hot-swap drive bays, Default 10 SATA3 ports (2 SATA3 ports for SATA DOM or internal HDD). Optional 24 SAS3 ports via AOC, Optional 20 SAS3 ports via AOC + 4 NVMe ports via AOC
System Memory		Power Supply	
Memory Capacity	48x 288-pin DDR4 DIMM slots, Up to 6TB ECC 3DS LRDIMM, Up to 3TB ECC LRDIMM, Up to 1.5TB ECC RDIMM	1000W High efficiency (96%) Redundant PSU; Titanium Level	
Expansion Slots		Cooling System	
PCI-Express	9 PCI-E 3.0 x8 slots, 2 PCI-E 3.0 x16 slots	4x 8cm heavy duty PWM fans	
Integrated On-Board		Form Factor	
SATA	SATA3 (6Gbps) with RAID 0, 1, 5, 10	Form Factor	2U Rackmount
LAN	4 RJ45 GbE LAN ports, 1 RJ45 Dedicated IPMI LAN port	Height	: 3.5" (89mm),
		Width	: 17.2" (437 mm),
		Depth	: 30.7" (780mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid Card	Optional		
Optical Drive	None		