

Tyrone Camarero Specifications

Tyrone

Camarero: RDA200A3A-48

Key Feature

- Supports Dual AMD EPYC 9004/9005 Processors
- Support Dual Passive GPUs of TDP Upto 350W
- Supports 8+8 DDR5 RDIMM Expandable Memory
- 5 x16 Expansion Slots
- Latest AST2600 BMC Controller iKVM, vMedia support
- Support 8 x 3.5"/2.5" Hot Swappable Bays
- Supports 2 x 5.25" ODD + 1 x Slim ODD
- Dual 10GbE(RJ45) by Intel X710-AT2
- Multiple PSU Options 800W/1300W/1600W 80+ CRPS
- Supports ATX PSU(1200W)



Processor/Cache		Drive bays	
Processor	Supports Dual AMD EPYC 9004/9005 Processors upto 360W TDP	HDD Bays	Supports 8 x (SAS/SATA) 2.5"/3.5" Hot Swappable Bays Supports 2 x 5.25" ODD + 1 x Slim ODD
System Memory		Power Supply	
Memory Capacity	Supports 8+8 DDR5 RDIMM Expandable Memory, Max Frequency 6400MHz Max Capacity 64GB/DIMM, Max System Memory 1TB	Power Supply	800W/1300W/1600W 80+ CRPS 1200W Single ATX
Expansion Slot		Security	
PCI-Express	3 x16 PCIe5.0 + 2 x16 PCIe4.0 3 MCIO PCIe 5.0 x8	TPM	TPM 2.0
Ports		Form Factor	
Ports	1 x RJ45 GbE connector for BMC dedicate management port (RTL8211E) 2 x 10GbE (RJ45) by Intel®X710-AT2 2 x USB 3.0 Type A Ports (Front) 2 x USB3.2 Gen1 type-A Ports (Rear) 1 x DB-15 VGA connector 1 x external UID/switch button	Form Factor	4U Rackmount
Front LEDs		Dimensions	
Front LEDs	1 x Power LED Button 1 x Alert LED 1 x HDD Activity 2 x LAN Activity 1 x Reset Button 1 x UID Button	Dimensions	680 x 438 x 175 mm
		Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com	