

Tyrone Camarero Specifications

Tyrone

Camarero: RDA200A3R-212

Key Feature

- Supports Dual AMD EPYC 9004/9005 Processors
- Supports 8+8 DDR5 RDIMM Expandable Memory
- 5 x16 Expansion Slots
- Latest AST2600 BMC Controller iKVM, vMedia support
- Support 12 x 3.5"/2.5" Hot Swappable Bays
- Dual 10GbE(RJ45) by Intel X710-AT2
- Multiple PSU Options 800W/1300W/1600W 80+ CRPS



Processor/Cache

Processor Supports Dual AMD EPYC 9004/9005 Processors upto 360W TDP

System Memory

Memory Capacity Supports 8+8 DDR5 RDIMM Expandable Memory
Max Frequency 6400MHz
Max Capacity 64GB/DIMM,
Max System Memory 1TB

Expansion Slot

PCI-Express 3 x16 PCIe5.0 + 2 x16 PCIe4.0
3 MCIO PCIe 5.0 x8

Ports

Ports 1 x RJ45 GbE connector for BMC dedicate management port (RTL8211E)
2 x 10GbE (RJ45) by Intel®X710-AT2
2 x USB 3.0 Type A Ports (Front)
2 x USB3.2 Gen1 type-A Ports (Rear)
1 x DB-15 VGA connector
1 x external UID/switch button

Front LEDs

Front LEDs 1 x Power LED Button
1 x Alert LED
1 x HDD Activity
2 x LAN Activity
1 x Reset Button
1x UID LED Button

Drive bays

HDD Bays Supports 8 x (SAS/SATA) + 4 x (SAS/SATA/NVMe) 2.5"/3.5" Hot Swappable Bays

Power Supply

Power Supply 800W/1300W/1600W 80+ CRPS

Security

TPM TPM 2.0

Form Factor

Form Factor 2U Rackmount

Dimensions

Dimensions 660 x 436 x 87 mm

Email : Info@tyronesystems.com

For more/current product information, Visit
www.tyronesystems.com