Tyrone Camarero Specifications



Camerero: RDA200A3R-28

Key Feature

- Supports Dual AMD EPYC 9004/9005 Processors
- Supports 8+8 DDR5 RDIMM Expandable Memory
- 5 x16 Expansion Slots
- Latest AST2600 BMC Controller iKVM, vMedia support
- Support 8 x 3.5"/2.5" Hot Swappable Bays
- Dual 10GbE(RJ45) by Intel X710-AT2
- Multiple PSU Options 800W/1300W/1600W 80+ CRPS





Processor/Cach

Supports Dual AMD EPYC 9004/9005 **Processor**

Processors upto 360W TDP

System Memory

Memory Capacity Supports 8+8 DDR5 RDIMM Expandable Memory, Max Frequency 6400MHz Max Capacity 64GB/DIMM, Max System Memory 1TB

Expansion Slot

PCI-Express

3 x16 PCle5.0 + 2 x16 PCle4.0

3 MCIO PCIe 5.0 x8

Ports

Ports

1 x RJ45 GbE connector for BMC dedicate management port (RTL8211E) 2 x 10GbE (RJ45) by Intel®X710-AT2 2 x USB 3.0 Type A Ports (Front) 2 x USB3.2 Gen1 type-A Ports (Rear)

1 x DB-15 VGA connector 1 x external UID/switch button

Front LEDs

Front LEDs

1x Power LED Button 1x HDD Activity 1 x LAN Activity 1 x Alert LED 1x UID LED Button 1x Reset Button

Drive bays

HDD Bays

Supports 8 x (SAS/SATA) 2.5""/3.5"" Hot

Swappable Bays 4 x 2.5" Internal Drives 1 x Slim DVD-ROM

Power Supply

Power Supply

800W/1300W/1600W 80+ CRPS

Security

TPM

TPM 2.0

Form Factor

Form Factor

2U Rackmount

Dimensions

Dimensions

680 x 430 x 88 mm

Email: Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com

AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries
Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners