

# Tyrone Camarero Specifications

Tyrone

## Camerero: RSI100A3R-212

### Key Feature

- 3rd Gen Intel® Xeon Single Processor
- 8 x DDR4, Max 3200Mhz,RDIMM: up to 64GB/DIMM, RDIMM/LRDIMM-3DS: up to 256GB/DIMM
- 4 x16 PCIe4.0, 3 x8 PCIe4.0 + 2,1 x M.2 PCIe Gen3.0 x4 , 1 x M.2 PCIe Gen3.0 x1
- 1 Mini-SAS HD + 8 SATA 7-pin (Intel® C621A : RAID 0/1/5/10)
- 1 x RJ45 GbE connector for BMC dedicate management port
- 2 x Intel® i210 1GbE (RJ45)
- 4 x USB3.2 Gen1 type-A connector at rear I/O, 1 x USB3 pin header supports two USB3.1 Gen1
- 12 x front loaded 2.5"/3.5" bays(SAS/SATA)
- Support CRPS PSU(FSP) 800W/1200W/1600W



Processor/Cache	Drive bays
<b>Processor</b> 3rd Gen Intel® Xeon Single Processor	<b>HDD Bays</b> 12 x 3.5 /2.5(SAS/SATA) Hot Swappable Bays
System Memory	Power Supply
<b>Memory Capacity</b> 8 x DDR4, Max 3200Mhz,RDIMM: up to 64GB/DIMM, RDIMM/LRDIMM-3DS: up to 256GB/DIMM	<b>Power Supply</b> Support CRPS PSU(FSP) 800W/1200W/1600W
Expansion Slot	Form Factor
<b>PCI-Express</b> 4 x16 PCIe4.0, 3 x8 PCIe4.0 + 2,1 x M.2 PCIe Gen3.0 x4 , 1 x M.2 PCIe Gen3.0 x1	<b>Form Factor</b> 2U Rackmount
Integrated Onboard:	Dimensions
<b>SAS/SATA Storage</b> 1 Mini-SAS HD + 8 SATA 7-pin (Intel® C621A : RAID 0/1/5/10)	<b>Dimensions</b> 660 x 436 x 87 mm
Front Panel	<b>Email : <a href="mailto:Info@tyronesystems.com">Info@tyronesystems.com</a></b> <b>For more/current product information, Visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b>
<b>Ports</b> 4 x USB3.2 Gen1 type-A connector at rear I/O, 1 x USB3 pin header supports two USB3.1 Gen1, 1 x DB-15 VGA connector, 1 x COM connector, 1 x external UID/switch button	

• Intel, the Intel logo,the Intel Inside logo,Xeon,and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/Or other Countries  
• Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the properties of their respective owners