

Tyrone Camarero Specifications

Tyrone

Camerero: RSI200A3A-44

Key Feature

- Single Socket LGA 1700,i7-14700 Supported
- Intel W680
- 4 DIMM slots (2DPC) , Max Memory/DIMM : 48GB on Intel® Core™ 14th Gen, 13th Gen Intel® Core™ processor, 32GB on 12th Gen Intel® Core™ processors
- Nvidia Geforce rtx 4060 ti 8gb Supported
- 1 PCIe5.0 x16,1 PCIe5.0 x8,2 PCIe4.0 x4
- VGA, 1 HDMI, 1 DisplayPort, 7.1 CH HD Audio Codec (HD Audio Jacks: Optical SPDIF Out Port, Line Out Jack, Microphone Input Jack)
- 4 x RJ45(1GbE)
- 1x2.5" + 4x3.5"HDD Bay (fix Bays)
- ATX PSU 500W PWS
- Storage Temperature : 0°C(32°F) ~ 50°C(122°F) ,Humidity : 5% ~ 95% non-condensing
- Operating Temperature: 10°C ~ 35°C /Non Operating Temperature: -40°C ~ 70°C
- Non operating Humidity : 20% ~ 90% (non-condensing)



Processor/Cache	
Processor	Single Socket LGA 1700,i7-14700 Supported
Chipset	
Chipset	Intel W680
System Memory	
Memory Capacity	4 DIMM slots (2DPC) , Max Memory/DIMM : 48GB on Intel® Core™ 14th Gen, 13th Gen Intel® Core™ processor, 32GB on 12th Gen Intel® Core™ processors
Expansion Slots	
Expansion Slots	1 PCIe5.0 x16,1 PCIe5.0 x8,2 PCIe4.0 x4

Ports	
Ports	1 VGA, 1 HDMI, 1 DisplayPort, 7.1 CH HD Audio Codec (HD Audio Jacks: Optical SPDIF Out Port, Line Out Jack, Microphone Input Jack), 2 Type A (USB3.2 Gen1)
Drive bays	
HDD Bays	1x2.5" + 4x3.5"HDD Bay (fix Bays)
Power Supply	
Power Supply	ATX PSU 500W PWS
Form Factor	
Form Factor	4U Rackmount
Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com	