Tyrone Camarero Specifications

Camerero: RSI20F0A-48

Key Feature

- Single Intel® Xeon® W-2500/2400 and W-3500/3400 series processors
- Intel® W790
- 8 x DDR5 4400MT/s (2DPC) / 4800MT/s (1DPC)
- 4 x16 PCIe5.0
- Intel® W790 (Up to 8 SATA 6Gb/s; RAID 0/1/5/10) : 1 OCuLink for 4 SATA + 4 SATA 7-pin
- 1 x RJ45 GbE connector for BMC dedicate management port, 2 x 10GbE (RJ45),1 x 2.5GbE (RJ45) ,1 x 1GbE (RJ45) 2 x USB3.2 Gen1 type-A Port, 1 x DB-15 VGA connector, 1 x DB9 COM connector, 1 x USB 3.2 Gen1 Header to support two Front USBs, 1 x external UID/switch button
- 8 x 3.5"/2.5"(SATA) Fix/Hotswappable disks
- 1200W/1600W/2000W Power Supply

Processor/Cache	
Processor	Single Intel® Xeon® W-2500/2400 and W-3500/3400 series processors

Chipset	
Chipset	Intel® W790

System Memory	
Memory Capacity	8 x DDR5 4400MT/s (2DPC) / 4800MT/s (1DPC)

Expansion Slot	
PCI-Express	4 x16 PCIe5.0

Ports	
Ports	1 x RJ45 GbE connector for BMC dedicate management port, 2 x 10GbE (RJ45),1 x 2.5GbE (RJ45) ,1 x 1GbE (RJ45) 2 x USB3.2 Gen1 type-A Port, 1 x DB-15 VGA connector, 1 x DB9 COM connector, 1 x USB 3.2 Gen1 Header to support two Front USBs, 1 x external UID/switch button

Drive bays	
HDD Bays	8 x 3.5"/2.5"(SATA) Fix disks

Power Supply	
Power Supply	1200W/1600W/2000W Power Supply

Form Factor	
Form Factor	4U Rackmount

Dimensions	
Dimensions	680 x 438 x 175 mm

Email : Info@tyronesystems.com

For more/current product information, Visit

www.tyronesystems.com