

Tyrone Camarero Specifications

Tyrone

Camarero: RSI210A3A-48

Key Feature

- Supports Single Intel®Xeon®W-2500/2400 and W-3500/3400 series processors
- Support Dual Passive GPUs of TDP Upto 350W
- Supports 8 x DDR5 RDIMM Expandable Memory
- 4 x16 PCIe 5.0 Expansion Slots
- Latest Aspeed AST2600 BMC Controller
- Support 8 x 2.5"/3.5" SAS/SATA Hot Swappable Drives
- Supports 2 x 5.25" ODD + 1 x Slim ODD
- 80+ CRPS & Single Power Supply
- Enhanced Security with TPM 2.0 and Chassis Intrusion



Processor/Cache	
Processor	Single Intel®Xeon®W-2500/2400 and W-3500/3400 Series Processors of TDP Upto 350W (Socket E (LGA 4677))
Chipset	
Chipset	Intel®W790
System Memory	
Memory Capacity	8 x DDR5 4400MT/s (2DPC) / 4800MT/s (1DPC) RDIMM: 64GB RDIMM-3DS: 2H-128 GB/ 4H-256 GB Max System Memory : 2TB
Expansion Slot	
PCI-Express	4 x16 PCIe5.0 FHFL Slots
Ports	
Ports	1 x RJ45 GbE connector for BMC dedicate management port (RTL8211E) (Rear) 2 x 10GbE (RJ45) by Broadcom BCM57416 (Rear) 1 x 2.5GbE (RJ45) by Intel i226 (Rear) 1 x 1GbE (RJ45) by Intel i210 (Rear) 2 x USB3.2 Gen1 type-A Ports (Rear) 1 x DB-15 VGA connector, 1 x DB9 COM connector (Rear) 1 x USB 3.2 Gen1 USBs (Front) 1 x external UID/switch button (Rear)
Indicators	
Indicators	1 x Power LED Button 1 x Alert LED 1 x HDD Activity 2 x LAN Activity 1 x Reset Button 1 x UID Button

Drive bays	
HDD Bays	Supports 8 x (SAS/SATA) 2.5"/3.5" Hot Swappable Bays Supports 2 x 5.25" ODD + 1 x Slim ODD
Security	
Security	Chassis Intrusion TPM 2.0
Power Supply	
Power Supply	800W/1300W 80+ CRPS Certified 500W/1200W ATX Single Power Supply (Optional)
Environment	
Environment	System Operating Temperature: 0°C ~ 35°C Non-operating Temperature: -20°C ~ 70°C Non-operating Relative Humidity: 5% ~ 85% (non-condensing)
Form Factor	
Form Factor	4U Rackmount/Tower
Dimensions	
Dimensions	438mm(W) x 175mm(H) x 680mm(D)
Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com	